

QuestSpecialty

GENESIS

Penetrating Lubricant

GENESIS

Penetrating Lubricant
Lubricante Penetrante

Non-Flammable
Non-Chlorinated
Non-Conducting
Four Way Protection
Prevents Rust &
Displaces Moisture

DANGER/PELIGRO:
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.
CONTIENE GAS A PRESIÓN; PUEDE
EXPLOTAR SI SE CALIENTA.

NET WT. 15 OZ. (425 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
800.231.0454 • www.questspecialty.com

CORRODED SURFACES: Will loosen dirt and scale from painted and plated surfaces. Remove loosened scale and spray again to cover surface. **TO LOOSEN**

BOUND PARTS: Liberal application will loosen threads, tightly fitted parts, sliding and rotating parts, bolts, hinges and pins which have been "frozen" by corrosion. The formula will protect against renewed corrosion. Is a powerful, multiple-action protective shield against the harmful effects of moisture and corrosion. It protects electrical gear, metal and other surfaces from deterioration by displacing water and moisture and sealing all surfaces with a complete molecular film. It preserves equipment, thus reducing repair and maintenance costs. Also lubricates, loosens dirt, scale and other corrosive elements; never becomes dry, brittle or hard. Protects the properties of insulating substances and does away with wicking. The conductivity of commutators and contacts is protected by the formula. Can be used on either dry or wet surfaces. To ensure adequate protection, periodic checks should be made to determine the need for reapplication.

DIRECTIONS: Spray liberally directly on area to be treated. Reapply periodically as required.

MODO DE EMPLEO: Rocíe libremente sobre el área que se va a tratar. Repita periódicamente según se requiera.

DANGER: Contains gas under pressure; may explode if heated. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye protection.


If exposed or concerned: Get medical advice or attention. Dispose of contents and container in accordance with local, state, and federal regulations.

PELIGRO: Contiene gas a presión; Puede explotar si se calienta. Se sospecha que daña la fertilidad o al feto. Puede ser fatal en caso de ingestión y entra por las vías respiratorias.

Mantenga lejos de calor, chispas, llamas abiertas, y superficies calientes. -No fumar. No pulverice en llamas abiertas u otra fuente de ignición. Envase presurizado: No perforo ni queme, incluso después de usar. Proteja de la luz solar. No exponga a temperaturas que excedan 50°C/122°F. Almacene en un lugar bien-ventilada. Si se ingiere: Llame inmediatamente a un centro de control de venenos. NO induzca vomito. Obtenga instrucciones especiales antes de su uso. No manipule hasta que se hayan leído y comprendido todas las precauciones de seguridad. Use guantes protectores, ropa protectora y protección para los ojos. Si ha estado expuesto o preocupado: busque atención o consejo médico. Elimine el contenido y envase de acuerdo con las ordenanzas locales, estatales, y reglamentos federales.

CONTAINS (CAS#): Distillates (petroleum), hydrotreated light (64742-47-8), White mineral oil (8042-47-5), Dipropylene glycol monomethyl ether (34590-94-8), Octamethylcyclotetrasiloxane (556-67-2), Carbon dioxide (124-38-9).

| | |
|--------------|---|
| HEALTH | 1 |
| FLAMMABILITY | 1 |
| REACTIVITY | 0 |
| PERSONAL | B |



ITEM 533000001-20AR Made in USA



SDS AND
PRODUCT INFO

