

QuestSpecialty

LIBERATE
Penetrant

LIBERATE

Penetrant
Penetrante

Contains PTFE & Moly for High Pressure Performance & Decreased Metal Wear

Clinging Formula for Improved Lubricity & Coverage

Does not Contain Silicone or Chlorinated Solvents

DANGER/PELIGRO:

EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. AEROSOL EXTREMADAMENTE INFLAMABLE. CONTIENE GAS A PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA.

NET WT. 11 OZ. (312 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
800.231.0454 • www.questspecialty.com

SDS AND
PRODUCT INFO



Scientifically formulated penetrating oil and rust dissolver containing micron size particles of PTFE and Moly. This super penetrant carries the PTFE and molybdenum disulfide particles into the threads, crevices, etc. These particles act as millions of tiny ball bearings to prevent seizing and galling while the parts are being removed. This product is designed to be used on all dismantling jobs throughout the plant, shop or wherever parts are frozen or hard to operate. Quickly loosens corroded nuts, studs, bolts, flanges and pipe joints. Does not contain silicone or chlorinated solvents.

DIRECTIONS FOR USE: Shake well. Remove protective cap and point spray opening in desired direction. Holding container 6-12 inches from surface to be treated, spray product liberally, saturating joints. Allow to set 5-10 minutes and break out. For extremely difficult jobs, saturate joints and allow to set 5-10 minutes, then tap lightly with a hammer and break out.

MODO DE EMPLEO: Agite bien antes de usar. Remueva la tapa protectora y apunte en la dirección deseada. Sostenga el contenedor de 6 a 12 pulgadas de la superficie que se va a tratar, rocíe el producto con libertad hasta saturar las juntas. Espere de 5 a 10 minutos para desatorar. Para trabajos extremadamente difíciles, sature las juntas y permita que actúe de 5 a 10 minutos, después golpee ligeramente con un martillo para desatorar.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.


PELIGRO: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y penetración en las vías respiratorias. Mantener alejado del calor, chispas, llamas abiertas y superficies calientes. -No Fumar. No rocíe sobre una llama abierta u otra fuente de ignición. Envase a presión: No perforar ni quemar, incluso después de su uso. Proteger de la luz solar. No exponer a temperaturas superiores a 50°C/122°F. Almacenar en un lugar bien ventilado. Lávese bien las manos después de manipular. Si se ingiere: Llame inmediatamente a un centro de intoxicaciones o a un médico. No induzca el vomito. Deseche el contenido y el contenedor de acuerdo con las regulaciones locales, estatales y nacionales.

WARNING: Cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ADVERTENCIA: Cáncer, defectos de nacimiento u otros daños reproductivos. Para obtener más información, visite www.P65Warnings.ca.gov.

CONTAINS (CAS#): Distillates (petroleum), hydrotreated light (64742-47-8), Mineral Seal Oil (64741-44-2), Propane (74-98-6), Ethyl Acetate (141-78-6), Mineral Spirits (8052-41-3).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	A



ITEM 561200001-16AR

Made in USA



600055612