

# UNPLUG II

## CONTACT & CIRCUIT BOARD CLEANER



### DESCRIPTION

**UNPLUG II** is a highly effective blend of solvents that are fast drying, non-conductive and safe to use on metal. This product works quickly to remove oil, grease, dirt and grime from circuit boards, computers, magnetic tapes, printed circuits, gauges, switches and relays. Does not contain CFC's or HCFC's and is ozone safe. This product is extremely flammable and must only be used on equipment that has been de-energized. It also must be allowed to dry and fumes evacuated from equipment before re-energizing.

### APPLICATIONS

For electronic motors, electronic parts, refrigeration units, metal surfaces, computers, typewriters, and TV tuners. Can be used by offices, factories, machine shops, industrial plants, schools and hospitals.

### FEATURES & BENEFITS

- Fast evaporation
- Residue free
- Dielectric to 25,000 volts
- Ozone safe
- No CFCs or HCFCs

### SPECIFICATIONS

**FORM:** Solvent Based Aerosol  
**ODOR:** Solvent  
**COLOR:** Clear Water White  
**DETERGENCY:** None  
**TOXICITY:** 500 ppm OSHA PEL  
**WETTING ABILITY:** Saturates  
**STORAGE STABILITY:** 1 Year  
**COLD STABILITY:** 0°F  
**PHOSPHATES:** None

**FLASH POINT:** Not Tested  
**FLAME EXTENSION:** >18"  
**SOLUBILITY IN WATER:** 10%  
**SPECIFIC GRAVITY:** 0.71  
**% VOC:** 74%  
**pH:** N/A  
**PROPELLANT:** 1,1-difluoroethane  
**EVAPORATION RATE:** Fast  
**BIODEGRADABILITY:** None

### LABEL INFORMATION

#### UNPLUG II CONTACT & CIRCUIT BOARD CLEANER


A highly effective blend of solvents that are fast drying, non-conductive and safe to use on metal. Does not contain CFC's or HCFC's and is ozone safe. Use to remove dirt, grease, oil, and grime from circuit boards, computers, magnetic tapes, printed circuits, gauges, switches and relays.

**DIRECTIONS:** This product is extremely flammable and equipment **MUST** be de-energized before using. Shake well and point spray nozzle toward surface to be cleaned. Spray until saturated using a cloth or brush to loosen soil. Reapply if necessary. Allow product to dry and fumes to be completely evacuated before equipment is re-energized.

**DANGER:** EXTREMELY FLAMMABLE. Equipment **MUST** be de-energized before using. Do not use near sparks, heat or open flame. Use only in a well ventilated area. Contents under pressure. Keep out of reach of children. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

**CONTAINS (CAS#):** Heptane (142-82-5), Isopropyl Alcohol (67-63-0), Acetone (67-64-1), 1,1-difluoroethane (75-37-6).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	B



### PACKAGING INFORMATION

12 – 16 oz. cans per case, 11 oz. net weight.  
 Private Label Only.