

Technical Data Report

TOUGH GUY

SUPER CONCENTRATED DEGREASER & TAR REMOVER



DESCRIPTION

TOUGH GUY degreases motors on automobiles, trucks, tractors, lawn mowers, boats, etc. Emulsifies tar, asphalt, bitumen and asphalt base plastic cements and mono-form roofing compounds used by roofers.

APPLICATIONS

Excellent for degreasing industrial machinery, lawn and turf equipment, municipal equipment, concrete floors and driveways, boat bilges, vertical surfaces, ceilings, engines, tools and hard-to-reach areas. Removes tar, asphalt and grease from all types of vehicles, equipment and masonry surfaces such as brick, stone, concrete, metals, ceramic tile, quarry tile, etc.

FEATURES & BENEFITS

- Jelled formulation – will not run
- Pleasant citrus fragrance
- No acids, alkalis, chlorinated or fluorinated solvents

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Citrus
COLOR: Tan Gel
DETERGENCY: None
TOXICITY: N/A
WETTING ABILITY: None
STORAGE STABILITY: 1 Year +
COLD STABILITY: 32°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: 18" +
SOLUBILITY IN WATER: Non-soluble
SPECIFIC GRAVITY: 0.875
% VOLATILE BY VOLUME: 95%
pH: N/A
PROPELLANT: 152
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

LABEL INFORMATION

TOUGH GUY SUPER CONCENTRATED DEGREASER AND TAR REMOVER

TOUGH GUY degreases motors on automobiles, trucks, tractors, lawn mowers, boats, etc. Excellent for degreasing industrial machinery, lawn and turf equipment, municipal equipment, concrete floors and driveways, boat bilges, vertical surfaces, ceilings, engines, tools and hard-to-reach areas. Removes tar, asphalt and grease from all types of vehicles, equipment and masonry surfaces such as brick, stone, concrete, metals, ceramic tile, quarry tile, etc. Emulsifies tar, asphalt, bitumen and asphalt base plastic cements and mono-form roofing compounds used by roofers.


DIRECTIONS: Shake well before using. For Engines: Spray area to be degreased thoroughly by pushing straight down on the valve button at the top of the can. Let it set for 10 to 20 minutes. Hose off with strong stream of water. Idle engine for 15 minutes immediately after hoseoff to assure complete drying. For Industrial Machinery: Spray area to be degreased thoroughly by pushing straight down on the valve button at the top of the can. Let it set for 10 to 20 minutes. Wash equipment thoroughly and rinse with potable water before returning it to processing area. For Tar & Asphalt Removal: Spray area to be degreased and let it set at least 10 minutes. Agitate if necessary and hose off with water. Note: Always test product in an inconspicuous area before using.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

CONTAINS (CAS#): Petroleum distillates, hydrotreated light (64742-47-8); Methyl Soyate (67784-80-9), (R)-p-mentha-1,8-diene (5989-27-5), Butoxydiglycol (112-34-5); 1,1-Difluoroethane (75-37-6).

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 20 oz. cans per case, 17 oz. net weight.