

Technical Data Report

MISTER BLISTER

METHYLENE CHLORIDE FREE PAINT REMOVER



DESCRIPTION

MISTER BLISTER is a gel-based paint remover. The methylene chloride free formula is a safer alternative to paint removal. Penetrates deep to remove paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials from all surfaces. Washes off with water or solvent. Safe to use on metal, brick, ceramic, wood and tile surfaces. Clings to all vertical surfaces.

APPLICATIONS

Works hard to remove paint, lacquer, carbon deposits and silicone. Areas of use include auto dealers, paint shops, factories, schools, farms, oil rigs, bottling plants, lumber mills and cement plants.

FEATURES & BENEFITS

- Gel-based formula clings to vertical surfaces, allowing longer contact time
- Removes a wide range of paints and surface sealers from metal, concrete and wood
- Ease of use—simply spray on and wipe or rinse

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Acetone
COLOR: Blue-Green
DETERGENCY: Strong
TOXICITY: 1000 ppm
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
% VOC's: 48%

FLASH POINT: N/A
FLAME EXTENSION: None
SOLUBILITY IN WATER: 100%
SPECIFIC GRAVITY: 0.95-0.98
% VOLATILE BY VOLUME: 79%
pH: N/A
PROPELLANT: Hydrocarbon
VISCOSITY: 100-300 cps
BIODEGRADABILITY: No

LABEL INFORMATION

MISTER BLISTER METHYLENE CHLORIDE FREE PAINT REMOVER

Gel formulation paint remover quickly removes paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run.

FOR USE BY: Auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices.


FOR USE ON: Metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry & cylinders.

DIRECTIONS: Shake well before using. Holding can 8-10 inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow product to complete blistering before removing.

DANGER: Extremely flammable aerosol. Contains gas under pressure; May explode if heated. Causes serious eye damage. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. **IF ON SKIN:** Take off Immediately all contaminated clothing. Immediately rinse with water for several minutes. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical help. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately. Specific treatment (see First Aid Measures section of this SDS). **IF IN EYES:** Immediately rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Use only outdoors or in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed.

CONTAINS (CAS#): Acetone (67-64-1), Dioxolane (646-06-0), Propane/n-Butane (68476-86-8), Monoethanolamine (141-43-5), Isopropylidene Glycol (100-79-8).

HEALTH	3
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 16 oz. cans per case, 11 oz. net weight