

UNPLUG

FAST EVAPORATING INDUSTRIAL DEGREASER



DESCRIPTION

UNPLUG removes oil, grease, tar and lubricants. Solvents evaporate completely leaving no residues on cleaned surfaces. Due to VOC regulations, not available for sale in CA, CT, MD, PA, NJ, OH, MA, ME, MI, NY, DE, VA, DC, NH, IL, IN, UT.

APPLICATIONS

For use on circuit boards, electrical contacts, electric motors, machinery parts, electronic equipment, molds, textiles and more. For use in automotive repair shops, electric services, electrical contracting, electronic computing equipment, fabricated metal products, heating and air conditioning services and more.

FEATURES & BENEFITS

- Removes oil, grease, tar & lubricants
- Versatile, non-corrosive formula
- Evaporates fast leaving no residue
- No chlorinated solvents

SPECIFICATIONS

<p>FORM: Solvent-Based Liquid ODOR: Solvent COLOR: Colorless DETERGENCY: None TOXICITY: 400 ppm OSHA PEL WETTING ABILITY: Saturates STORAGE STABILITY: 1 Year COLD STABILITY: 0°F PHOSPHATES: None</p>	<p>FLASH POINT: <20°F TCC FLAME EXTENSION: N/A SOLUBILITY IN WATER: 0% SPECIFIC GRAVITY: 0.71 % VOLATILE BY VOLUME: 100% pH: N/A VISCOSITY: Thin EVAPORATION RATE: Fast BIODEGRADABILITY: None</p>
---	--

LABEL INFORMATION

UNPLUG FAST EVAPORATING INDUSTRIAL DEGREASER

UNPLUG removes oil, grease, tar and lubricants. Solvents evaporate completely leaving no residues on cleaned surfaces.

FOR USE ON: Circuit boards, electrical contacts, electric motors, machinery parts, electronic equipment, molds, textiles and more.

FOR USE IN: Automotive repair shops, electric services, electrical contracting, electronic computing equipment, fabricated metal products, heating and air conditioning services and more.

DIRECTIONS: For light soils, spray onto surface and wipe clean. For heavy soils, saturate thoroughly and let stand 15-30 seconds. Flush with a second blast and wipe clean. **NOTE:** Before restarting electric motors, or exposing cleaned parts to extreme heat or possible sources of ignition, solvent must be completely evaporated. **NOTE:** This product is extremely flammable. Do not smoke or weld or allow any other type of ignition while using.


DANGER: Highly Flammable liquid and vapor. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Keep container tightly closed. Wear protective protective gloves and eye protection. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water or shower. If skin irritation occurs: Get medical advice or attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. In case of fire use dry chemical, foam, or carbon dioxide. Store in a well-ventilated place. Keep container tightly closed and cool. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Wash hands thoroughly after handling. Avoid breathing fumes, mist, or vapors. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

For large quantities: Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

CONTAINS (CAS#): Heptane (142-82-5), Isopropyl Alcohol (67-63-0).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

Available in 5 gallon pails and 55 gallon drums.