

QUIKLEEN II

SOLVENT CLEANER



DESCRIPTION

QUIKLEEN II is a USDA authorized non-flammable solvent cleaner. Has no flash point at any temperature. Medium evaporation—leaves no residue. Quickly dissolves grease, oils, soil and dirt. Excellent for electronic motor cleaning. Has a dielectric strength of 29,000 volts.

APPLICATIONS

Areas of use include industrial plants, machine shops, institutions, automotive industries and hospitals. QUIKLEEN II is specially formulated for use on electric motors even while running, gas engines, machinery, circuit boards, ignition systems, generators, power tools and electronic equipment.

FEATURES & BENEFITS

- Non-flammable
- Non-conductive
- Contains no Carbon Tetrachloride or 1,1,1 Trichloroethane
- Contains no oil—leaves no film
- 29,000 volt dielectric strength

SPECIFICATIONS

FORM: Solvent-Based Liquid	FLASH POINT: N/A
ODOR: Chlorinated Solvent	BOILING POINT: 250°F, 121°F
COLOR: Clear	SOLUBILITY IN WATER: 0%
DETERGENCY: N/A	SPECIFIC GRAVITY: 1.5
TOXICITY: 100 ppm OSHA PEL	% VOLATILE BY VOLUME: 100%
WETTING ABILITY: Saturates	pH: N/A
STORAGE STABILITY: 1 Year +	VISCOSITY: Thin
COLD STABILITY: 0°F	EVAPORATION RATE: Medium
PHOSPHATES: None	BIODEGRADABILITY: No

LABEL INFORMATION

QUIKLEEN II SOLVENT CLEANER

A highly concentrated solvent designed to remove dirt, grease, oil and grime from metallic and non-metallic surfaces. Cleaning is quick and simple without the danger of injury to working parts. Ideally suited for use on electric motors, even while running, electronic equipment, ignition systems, generators, power tools, etc. Also used on air conditioning, refrigeration and all types of mechanical equipment. USDA accepted for use in establishments operating under the Federal Meat and Poultry product inspection program of the USDA.

NOTE: Do not use on automated electronic process control or monitoring systems, computers, or data processing equipment. May effect certain plastics. Test before using.

DIRECTIONS

Brush or spray onto the surface to be cleaned or use in a vat for immersion cleaning. No special rinsing or flushing is necessary, although if desired, surfaces may be flushed with fresh solvent. Use without dilution and without heat. Repeat application if necessary for heavily encrusted soils.


FOR IMMERSION: Immerse for three to five minutes. Avoid prolonged immersion, as it could damage varnish, rubber or plastic parts. Use instead of carbon tetrachloride, kerosene, 1,1,1 trichloroethane, naphtha or other flammable solvents. When contaminated with soil, do not discard, just filter out the foreign matter and use it over again. Keep vat covered to avoid evaporation.

WARNING: Causes skin and eye irritation. Suspected of causing cancer. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, eye protection, and organic vapor respirator. If exposed or concerned: Get medical advice or attention. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Wash hands thoroughly after handling. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

WARNING: This product contains chemical(s) known to the State of California to cause cancer.

CONTAINS (CAS#): Tetrachloroethylene (127-18-4).

HEALTH	2
FLAMMABILITY	0
REACTIVITY	1
PERSONAL	G



PACKAGING INFORMATION

Available in 4 x 1 gallons (private label only), 5 and 6 gallon pails and 55 gallon drums.