

# RESTORE

## RUST CONVERTER & PROTECTIVE COATING

### DESCRIPTION

RESTORE stops further erosion and rusting of machinery, tools, vehicles, equipment, boats, metal buildings and more. When painted on, RESTORE chemically converts rust into a black organic complex. A clear acrylic coating is formed. The coating is sufficient to last for years without painting, or it can be painted over using latex, oil based or epoxy paint. Extends the life of anything made of metal.

### APPLICATIONS

For use by industrial plants, schools, institutions, office buildings, homes, farms and shipyards. Formulated for automobiles, boats, heavy equipment, metal buildings, tools and railroads.

### FEATURES & BENEFITS

- Oxidizes corrosion and scale
- Brightens surfaces
- Highly concentrated and powerful

### SPECIFICATIONS

FORM: Water-Based Liquid  
 ODOR: Odorless  
 COLOR: Milky Tan  
 DETERGENCY: N/A  
 TOXICITY: Non-hazardous  
 WETTING ABILITY: Excellent  
 STORAGE STABILITY: 1 Year +  
 COLD STABILITY: 35°F  
 % VOC: 1.8%

FLASH POINT: > 200°F (93.3°C)  
 BOILING POINT: >212°F  
 SOLUBILITY IN WATER: Miscible  
 SPECIFIC GRAVITY: 1.025  
 % VOLATILE BY VOLUME: N/A  
 pH: N/A  
 VISCOSITY: Thick  
 EVAPORATION RATE: Slow  
 BIODEGRADABILITY: No

### LABEL INFORMATION

#### RESTORE RUST CONVERTER & PROTECTIVE COATING

RESTORE stops further erosion and rusting of machinery, tools, vehicles, equipment, boats, metal buildings, and more. When painted on, Restore chemically converts rust into a black organic complex. A clear acrylic coating is formed. The coating is sufficient to last for years without painting, or it can be painted over using latex, oil based or epoxy paint. Extends life of anything made of metal.


**DIRECTIONS:** Shake well. Clean rusted surface of loose rust flakes with wire brush. Apply product at the rate of 300 to 500 sq. ft. per gallon. Apply by brushing, dipping, swabbing or spraying product evenly over rusted surface. May be applied using equipment designed to spray latex paint. If necessary, when spraying add up to 3 oz. of water per gallon. Allow to dry completely. A clear hard finish will form. Surface may be painted or left as is after drying. Do not store at 32°F or below.

**CAUTION:** KEEP OUT OF REACH OF CHILDREN. May be harmful if taken internally. Avoid contact with eyes. In case of contact, flush with water for 15 minutes and consult physician immediately.

 **WARNING:** Cancer - For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**CONTAINS (CAS):** Vinylidene chloride acrylic copolymer (N/A), Water (7732-18-5), Tannic acid (1401-55-4), 2-Butoxyethanol (111-76-2), Xanthan gum (11138-66-2).

HEALTH	0
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



### PACKAGING INFORMATION

Available in 12 x 1 quarts, 4 x 1 gallons, 5 and 6 gallon pails, and 55 gallon drums.