

QuestSpecialty

AVERT

Corrosion Inhibitor Inhibidor corrosivo

Non Drying Formula
Long Term Rust
Preventative Lubricant

WARNING/ADVERTENCIA:
FLAMMABLE AEROSOL. CONTAINS GAS
UNDER PRESSURE; MAY EXPLODE IF HEATED.
AEROSOLE INFLAMMABLE. CONTIENE
GAS A PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA.

NET WT. 11 OZ. (312 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
800.231.0454 • www.questspecialty.com

SDS AND
PRODUCT INFO



Avert will prevent rust and corrosion on all metal parts. Apply to machine parts, dies, pipe threads, casting, tools, jigs and stamped metal parts. Prevents corrosion due to salt spray on cables, hoists, pulleys, winches and riggings. Affords long term protection for indoor storage. Excellent for protecting materials while in transit. A 2 or 3 mil coating will provide protection for indoor storage for up to 2 years. Film is transparent, easy to see through. Can be removed by washing with kerosene or mineral spirits. Once removed, parts can be painted.

DIRECTIONS FOR USE: Product is most effective when parts are clean and free of rust, scale or dirt. Remove protective cap. Point opening in spray tip towards part to be coated. Holding can 8 to 10 inches from part, spray 2 or 3 mil coat with a slow sweeping motion. Completely wet surface.

INSTRUCCIONES DE USO: El producto es más eficaz cuando las piezas están limpias y libres de óxido, incrustaciones o suciedad. Retire la tapa protectora. Apunte la abertura en la punta del rociador hacia la parte a recubrir. Sosteniendo la lata de 8 a 10 pulgadas de la parte, rocíe una capa de 2 o 3 mil con un movimiento de barrido lento. Superficie completamente mojada.

WARNING: Flammable aerosol. Contains gas under pressure; may explode if heated.

Keep away from heat, sparks, open flames or hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

ADVERTENCIA: Aerosol inflamable. Contiene gas a presión; puede explotar si se calienta.

Mantener alejado del calor, chispas, llamas abiertas o superficies calientes. -No Fumar. No rocíe sobre una llama abierta u otra fuente de ignición. Envase presurizado: No perforar ni quemar, incluso después de su uso. Proteger de la luz solar. No exponer a temperaturas superiores a 50°C/122°F. Almacenar en un lugar bien ventilado.

CONTAINS (CAS): Distillates (petroleum), hydrotreated light CAS 64742-47-8, Carbon Dioxide CAS 124-38-9.

HMIS Ratings: Health 1, Flammability 2, Reactivity 0, Personal Protection B.

ITEM 561100001-16AR
Made in USA

