

QuestSpecialty

# BUOY



## BUOYING LIFT STATION CLEANER & DEGREASER

LIMPIADOR Y DESENGRASANTE DE  
ESTACIONES DE ASCENSO

Emulsifies & Liquefies  
Grease & Sludge

**DANGER/PELIGRO:**  
COMBUSTIBLE LIQUID.  
LÍQUIDO COMBUSTIBLE.

**NET CONTENTS: 5 GALLONS (18.9 L)**

### BUOY

- USE IN LIFT STATIONS, GREASE TRAPS, SEWAGE PITS, SUMPS, ETC.
- USE AT OFFICE BUILDINGS, SCHOOLS, APARTMENT COMPLEXES, HOSPITALS
- 100% BIODEGRADABLE
- ENVIRONMENTALLY SAFE
- DEGREASES, DEODORIZES & CLEANS

BUOY emulsifies and degreases raw sewage as it BUOYs into lift station wells. The accumulation of sewage, grease, oils, fatty acids, calcium, and soap scum forms deposits on wet well walls. BUOY leaves a pleasant citrus scent that effectively controls offensive odors.

Add BUOY directly to lift station wet wells in its concentrated form for effortless cleaning. Degreasing and cleaning are accomplished by the rise and fall of the water level. As the water level rises and lowers, BUOY removes the sludge from the sides of the walls, then "seals and contains" offensive odors from the lift station and totally eliminates the offensive job of cleaning lift station grease traps or sumps manually.

BUOY is biodegradable, non-freezing, contains no phosphates, no quaternary compounds, no chlorinated solvents, and is free from alkali and acids and will not inhibit waste digestion when used as directed.

**DIRECTIONS:** BUOY should be added to wet well until a layer of 8 to 12 inches is floating on the surface. This initial treatment should remain effective for a period of 3 to 6 months, depending on system demands. Add as needed.

**MODO DE EMPLEO:** BUOY de se añadido al contenedor hasta que se forme una capa de 8 a 12 pulgadas en la superficie. Este tratamiento inicial debe durar por un período de 3 a 6 meses, dependiendo de las demandas del sistema. Añada según se necesite.

**DANGER:** Combustible liquid. Causes skin irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Wear protective gloves and eye protection. Store in a well-ventilated place. Keep cool. Wash hands thoroughly after handling. Avoid breathing mist, vapors or spray. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. Contaminated work clothing must not be allowed out of the workplace. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and federal regulations.

**PELIGRO:** Líquido combustible. Causa irritación de la piel. Puede provocar una reacción alérgica en la piel. Pueden ser mortales si se ingieren y entra en las vías respiratorias. Mantener alejado de fuentes de calor, chispas, llamas y superficies calientes. -No fumar. Use guantes y protección ocular. Almacenar en un lugar bien ventilado. Mantener en un lugar fresco. Lávese bien las manos después de manipular. Evite respirar la niebla, los vapores o el aerosol. Si en la piel: Lavar con abundante agua. Si se produce irritación de la piel o sarpullido: Obtenga asesoramiento o atención médica. Quítese la ropa contaminada y lávela antes de reutilizarlo. La ropa de trabajo contaminada no se debe permitir fuera del lugar de trabajo. En caso de ingestión: Llame inmediatamente a un centro de envenenamientos o el médico. No se debe inducir el vómito. Disponer de contenido y contenedor en conformidad con los usos locales, estatales y federales de reglamentación.

420 grams per liter VOC.

**Contains (CAS#):** Distillates (petroleum), hydrotreated light (64742-47-8); Methyl 9-Decenoate (25601-41-6); 1,8-p-Menthadiene (5984-27-5).

**HMIS Ratings:** Health - 1, Flammability - 2, Reactivity - 0, Personal - B.

#### QuestSpecialty Corporation

P.O. Box 624 • Brenham, TX 77834  
800.231-0454 • www.questspecialty.com

ITEM 60500001-05PL

Made in USA

