

QuestSpecialty



Amber Premium Lithium
E.P. Grease



Amber Premium Lithium E.P. Grease

Amber Premium Grasa Litio E.P.

**Resists Thinning or Hardening in
Medium-Sized High Speed Bearings**

**Lithium Grease with
Oxidation Inhibitors & Extreme Pressure
Additives for a Wide Range of Uses**

Protects Surfaces Against Corrosion

Operating Range of 0°F to 350°F

CAUTION / PRECAUCIÓN:

KEEP OUT OF REACH OF CHILDREN

SEE ADDITIONAL CAUTIONS ON BACK PANEL

NO SE DEJE AL ALCANCE DE LOS NIÑOS

VEA PRECAUCIONES ADICIONALES EN EL PANEL TRASERO

NET CONTENTS: 14 OZ. (397 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
800.231.0454 • www.questspecialty.com

SDS AND
PRODUCT INFO



A multi-use lithium-complex grease for hundreds of automotive, marine, industrial and agricultural applications. Does not dry out after use as some clay based greases do. Remains pumpable at low temperatures.

Forms protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This waterproof lubricant will not wash out.

USES: Ball bearings, roller bearings, couplings, mechanical linkages, pumps, universal joints, ball joints, fifth wheels, wheel bearings, construction equipment, trucks, buses and farm tractors.

DIRECTIONS FOR USE: Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings: Fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

MODO DE EMPLEO: Inyecte grasa nueva hasta que la grasa vieja salga. Remueve la grasa vieja si es posible. Para conexiones de tipo bola: Llene hasta que la grasa vieja salga. Limpie las áreas expuestas con desengrasante para remover la grasa vieja. Inyecte nueva grasa.

vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

PRECAUCIÓN: No se deje al alcance de los niños. Puede causar irritación a los ojos. El contacto prolongado puede causar irritación de la piel. Si es ingerido, puede causar náusea, vomito y diarrea. Si hay contacto con los ojos, enjuague con agua, vea a un médico si la sensación aceitosa persiste. Si hay contacto con la piel, lave con agua y jabón. Para la ingestión de más de 8 onzas contate al médico.

CONTAINS (CAS#): Petroleum distillate, hydrotreated heavy naphthenic (64742-52-5), Lithium 12-hydroxystearate (7620-77-1), Lithium stearate (4485-12-5), Elco 102 (68649-42-3), Lubrizol 7065 OPC (N/A).

HMIS Ratings: Health - 0, Flammability - 0, Reactivity - 0, Personal - B.

NLGI GRADE: 2

ITEM L107

Made in USA

600005054

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea,

