

Safety Data Sheet

Pow

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Pow

PRODUCT CODE: 5016

RECOMMENDED USE: High Voltage Cable Cleaner and Electric Motor Degreaser

RESTRICTIONS ON USE: None known.

COMPANY NAME: QuestSpecialty Corporation

COMPANY ADDRESS: P.O. Box 624, Brenham, TX 77834

COMPANY PHONE: 800-231-0454

EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Gases Under Pressure: Compressed Gas

Acute Toxicity, Oral: Category 4

Skin Irritant: Category 2

Eye Irritant: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category 3

Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Rinse mouth. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state and federal regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
trans-1,2-Dichloroethylene	156-60-5	80-90%
1,1,2,2-Tetrafluoroethyl-2,2,2-trifluoroethylether	406-78-0	5-10%
Carbon dioxide	124-38-9	1-5%

SECTION IV - FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Seek medical attention if irritation persists.

INGESTION: Rinse mouth out with water. Do not induce vomiting unless directed by medical authority. Keep head below hips if vomiting occurs. Seek immediate medical attention. Aspiration hazard. Never give anything by mouth to an unconscious person.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration or at any sign of loss of consciousness seek immediate medical attention.

Safety Data Sheet

Pow

SKIN: Immediately wash with water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

ACUTE HEALTH HAZARDS: Causes skin irritation including redness, burning and drying/cracking. Causes eye irritation including redness, tearing, and pain. May cause respiratory irritation and central nervous system (CNS) depression. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration may cause pulmonary edema and pneumonitis.

CHRONIC HEALTH HAZARDS: May cause eye, respiratory and central nervous system (CNS) effects. Dermatitis may occur due to long-term irritation.

NOTE TO PHYSICIAN: Treatment of overexposure should be directed at the control of symptoms and the clinical condition. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide or water spray.

UNSUITABLE EXTINGUISHING MEDIA: Water jets or streams.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. Exposure to temperatures above 122 °F (50 °C) may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Vapors may form explosive mixtures with air. Vapors are heavier than air and can accumulate in low areas. Vapors may travel considerable distance to a source of ignition and flash back.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, hydrogen chloride, phosgene. Halogenated compounds. Smoke, toxic fumes and toxic gases.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Eliminate all sources of ignition. Wear appropriate personal protective equipment. Absorb with non-combustible material like vermiculite, sand or earth. Place waste in proper containers for waste disposal. Small releases may be wiped up with wiping material.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not reuse, puncture or incinerate container. Offer for recycling or wrap container and place in trash collection.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Do not use or store near heat, open flames or other sources of ignition. Wear proper personal protective equipment when using this product. Avoid contact with skin, eyes and clothing. Do not inhale mist or vapor. Do not use or store with strong oxidizers. Store in cool, dry, ventilated area. Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling.

OTHER PRECAUTIONS: Keep out of the reach of children. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.

INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, acids. Alkaline materials.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
trans-1,2-Dichloroethylene	200 ppm	200 ppm
1,1,2,2-Tetrafluoroethyl-2,2,2-trifluoroethylether	15 mg/3 (total dust)	50 ppm
Carbon dioxide	5000 ppm	5000 ppm

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area. Material may concentrate in low lying areas.

RESPIRATORY PROTECTION: Use only in well-ventilated areas. If exposure levels are exceeded, then organic vapor cartridge respirator or SCBA will be needed.

Safety Data Sheet

Pow

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles and chemical resistant gloves.

ADDITIONAL MEASURES: Avoid contact with skin, eyes or clothing. Wash hands thoroughly after handling. Do not breathe vapors.

Do not eat, drink, or smoke while using product. Get medical attention if you feel unwell. No smoking or open flames.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, colorless spray.

ODOR: Chlorinated solvent.

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: N/D

EVAPORATION RATE: N/D

FLAMMABILITY (solid/gas): Not considered a flammable aerosol or an extremely flammable aerosol by OSHA (29CFR 1910.1200).

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

EXPLOSIVE LIMIT LOWER (%): N/D

EXPLOSIVE LIMIT UPPER (%): N/D

VAPOR PRESSURE (mm Hg): N/D

VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H₂O=1): 1.25 - 1.35 @ 77 °F (25 °C).

SOLUBILITY(IES): N/D

PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D

AUTOIGNITION TEMPERATURE: N/D

DECOMPOSITION TEMPERATURE: N/D

VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: None known.

CHEMICAL STABILITY: Stable.

POSSIBLE HAZARDOUS REACTIONS: None known.

CONDITIONS TO AVOID: Temperatures greater than 122 °F (50 °C) and sources of ignition. Avoid incompatible materials.

INCOMPATIBLE MATERIALS: Strong oxidizing agents, strong reducing agents, acids. Alkaline materials.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, hydrogen chloride gas and phosgene gas.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **trans-1,2-Dichloroethylene** (156-60-5): LD₅₀ (Oral, Rat) 1235 mg/kg; LD₅₀ (Dermal, Rabbit) >5000 mg/kg; LC₅₀ (Inhalation, Rat, 4h) 24100 ppm. **Carbon dioxide** (124-38-9): LC₅₀ (Inhalation, Rat, 30m) 470,000 ppm.

ROUTES OF ENTRY: Eyes, Inhalation, Skin

EYES: Causes irritation, redness, tearing, pain.

INGESTION: Not a likely route of exposure under normal product handling conditions. May cause gastrointestinal irritation, nausea, diarrhea, vomiting. Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia or edema.

INHALATION: Causes respiratory tract irritation, dizziness, drowsiness.

SKIN: May cause irritation, localized defatting, dermatitis with prolonged or repeated contact.

MEDICAL CONDITION AGGRAVATED: Pre-existing disorders of the eyes, skin and central nervous system (CNS).

ACUTE HEALTH HAZARDS: Causes skin irritation including redness, burning and drying/cracking. Causes eye irritation including redness, tearing, and pain. May cause respiratory irritation and central nervous system (CNS) depression. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration may cause pulmonary edema and pneumonitis.

CHRONIC HEALTH HAZARDS: May cause eye, respiratory and central nervous system (CNS) effects. Dermatitis may occur due to long-term irritation.

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

Safety Data Sheet

Pow

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: **trans-1,2-Dichloroethylene** (156-60-5): EC₅₀ (*Daphnia magna*, 48h) 220 - 290 mg/L: NOEC (*Daphnia magna*, 48h) < 100 mg/L.

PERSISTENCE AND DEGRADABILITY: Not readily biodegradable.

BIOACCUMULATIVE POTENTIAL: This product is not expected to bioaccumulate.

MOBILITY IN SOIL: N/D

OTHER ADVERSE EFFECTS: None known.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not reuse, puncture or incinerate container. Offer for recycling or wrap container and place in trash collection.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, non-flammable.

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols.

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN1950

PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): **1,2-Dichloroethylene** (156-60-5)
Reportable Quantity = 1000 pounds.

SARA 311/312 HAZARD CATEGORIES: Gas under pressure. Acute toxicity (any route of exposure). Skin corrosion or irritation. Serious eye damage or eye irritation. Specific target organ toxicity (single or repeated exposure). Aspiration hazard.

SARA 313 REPORTABLE INGREDIENTS: This product does not contain any chemical components with known CAS numbers that exceed the threshold (*de minimis*) reporting levels established by SARA Title III, Section 313.

CLEAN WATER ACT: **trans-1,2-Dichloroethylene** (156-60-5) is a priority pollutant and a toxic pollutant.

STATE REGULATIONS: California Proposition 65: This product does not contain chemicals regulated by California Proposition 65.
trans-1,2-Dichloroethylene (156-60-5): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: MA, PA.

INTERNATIONAL REGULATIONS: Listed or exempt from listing/notification on the following chemical inventories: Domestic Substances List (DSL, Canada). Non-Domestic Substances List (NDSL, Canada).

VOLATILE ORGANIC COMPOUNDS (VOC): 85.5%

NFPA HEALTH: 2

NFPA FLAMMABILITY: 1

NFPA REACTIVITY: 0

NFPA OTHER: None

HMIS HEALTH: 2

HMIS FLAMMABILITY: 1

HMIS REACTIVITY: 0

HMIS PROTECTION: B

Safety Data Sheet

Pow

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Craig Bernard

DATE PREPARED: 02/19/2024

REVISION DATE: N/A

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.