



FREZE-IT CHEWING GUM REMOVER





DESCRIPTION

FREZE-IT offers an environmentally friendly alternative in gum and wax removal. A frosty blast of air in a can freezes gum and wax instantly, allowing it to be easily removed from many surfaces. Ideal for cooling circuit board components, soldering applications and shrink-fitting small parts. Non-corrosive.

APPLICATIONS

Excellent for use in schools, homes and welding shops. Works great on furniture, carpet, circuit boards, sidewalks, pins, bushings and bearings for easy removal of gum and wax.

FEATURES & BENEFITS

- · This formula freezes the gum which releases the adhesions between the gum or wax and the surface without the use of solvents
- · Fast acting
- Non-corrosive

SPECIFICATIONS

FORM: Solvent-Based Aerosol ODOR: None COLOR: Clear DETERGENCY: None TOXICITY: 1000 ppm OSHA TLV WETTING ABILITY: None

STORAGE STABILITY: 1 Year + COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: -155°F
FLAME EXTENSION: >18"
SOLUBILITY IN WATER: .008%
SPECIFIC GRAVITY: 0.56
% VOLATILE BY VOLUME: 100%

pH: N/A

PROPELLANT: Hydrocarbon EVAPORATION RATE: Fast BIODEGRADABILITY: No

LABEL INFORMATION

FREZE-IT CHEWING GUM REMOVER

A unique freezing agent gives fast easy removal of gum and wax deposits from carpet, upholstery, floors, furniture, walls, staircases and chairs. Quickly removes tackiness from gum and wax without harming, staining or marking painted surfaces. This product has been authorized by the USDA for use in federally inspected meat and poultry plants.

DIRECTIONS FOR USE: Remove cap and spray product on chewing gum or wax deposit for 20 to 30 seconds. Remove deposit by scraping with a spatula, spoon or knife. If initial application does not remove all the deposit, re-apply.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

CONTAINS (CAS#): Propane/n-Butane (68476-86-8).

HEALTH	1
FLAMMABILITY	4
REACTIVITY	0
PERSONAL	Α



PACKAGING INFORMATION