

MR. MECHANIC

LIQUID LUBRICANT



DESCRIPTION

MR. MECHANIC is a USDA authorized greaseless light duty lubricant for general use. Contains a light mineral oil in a petroleum distillate base with a corrosion preventative for long lasting protection. Lubricates, penetrates and prevents rust giving four-way protection.

APPLICATIONS

Lubricates and prevents corrosion of nuts, bolts, corroded parts, door hinges, locks, machine parts, gears, slides, wire cable, and other turning and sliding parts. For use around garages, oil rigs, homes, machine shops, assembly plants, electronics repair shops, service stations, locksmiths, industrial shops, factories, and air conditioner repair shops.

FEATURES & BENEFITS

- Loosens dirt and scale
- Four way protection - Lubricates, penetrates, displaces moisture, prevents corrosion.

SPECIFICATIONS

FORM: Solvent Based Liquid	FLASH POINT: >110°F
ODOR: Petroleum Solvent	FLAME EXTENSION: N/A
COLOR: Brown	SOLUBILITY IN WATER: 0%
DETERGENCY: None	SPECIFIC GRAVITY: 0.83
TOXICITY: 400 ppm OSHA TLV	% VOC: 7%
WETTING ABILITY: Saturates	pH: N/A
STORAGE STABILITY: 1 Year +	VISCOCITY: Thin
COLD STABILITY: 0°F	EVAPORATION RATE: Slow
PHOSPHATES: None	BIODEGRADABILITY: No

LABEL INFORMATION

MR. MECHANIC LIQUID LUBRICANT

MR. MECHANIC is a general purpose lubricant that provides four way action. It cleans, lubricates, penetrates and prevents rust. Will loosen dirt and scale from painted and plated surfaces. Remove loosened scale and spray again to cover surface.

TO LOOSEN BOUND PARTS: Liberal application will loosen threads, tighten fitted parts, sliding and rotating parts, bolts, hinges and pins which have been "frozen" by corrosion. The formula will protect against renewed corrosion.

Forms a powerful, multiple-action protective shield against the harmful effects of moisture and corrosion. It protects electrical gear, metal and other surfaces from deterioration by displacing water and moisture. It seals all surfaces with a complete molecular film. It preserves equipment, thus reducing repair and maintenance costs. Lubricates, loosens dirt, scale and other corrosive elements; never becomes dry, brittle or hard. Protects the properties of insulating substances and does away with wicking. The conductivity of commutators and contacts is protected by the formula. Can be used on either dry or wet surfaces. To insure adequate protection, periodic checks should be made to determine the need for reapplication.

LUBRICATES AND PREVENTS CORROSION OF: Nuts, bolts, corroded parts, door hinges, locks, machine parts, gears, slides, wire cable, and other turning and sliding parts.


FOR USE AROUND: Garages, oil rigs, homes, machine shops, assembly plants, electronics repair shops, service stations, locksmiths, industrial shops, factories, and air conditioner repair shops.

DIRECTIONS: Spray or brush on liberally directly on area to be treated. Reapply periodically as required.

DANGER: Combustible liquid. Causes serious eye irritation. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. In case of fire: Use dry chemical, foam or carbon dioxide (CO₂) to extinguish. Store in a well-ventilated place locked up. Keep cool. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

Contains (CAS#): Mineral Spirits (8052-41-3), Distillates (Petroleum), hydrotreated light (64742-47-8), Mineral Seal Oil (64741-44-2), Ethyl Acetate (141-78-6), Distillates (Petroleum), Solvent Dewaxed Heavy Paraffinic (64742-65-07).

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

Available in 5 gallon pails and 55 gallon drums.