

Product # 8095

Technical Data Report

FIFTY NIFTY PARTS CLEANER & DEGREASER



DESCRIPTION

An ultra-fast drying, no residue, cleaning solvent intended to degrease any non-painted metal surface. This heavy duty cleaning agent instantly removes oil, dirt build-up, varnish, sludge, grease and brake fluid. Contains no chlorinated solvents and is 50 state compliant. The powerful spray breaks through even the toughest deposits!

APPLICATIONS

Cleans and degreases engine parts, tools, equipment, farm equipment, carburetors and throttle bodies, brake and rotors or any other metal surface that needs degreasing FAST!

FEATURES & BENEFITS

- 50 State Compliant
- Ultra-Fast Dry Time
- No Residue Formula
- · Heavy Duty Cleaning Agent
- No Chlorinated Solvents

SPECIFICATIONS

FORM: Solvent Based Aerosol ODOR: Solvent COLOR: Clear DETERGENCY: None TOXICITY: 500 ppm OSHA PEL WETTING ABILITY: Saturates STORAGE STABILITY: 1 Year + COLD STABILITY: 0°F PHOSPHATES: None FLASH POINT: N/A FLAME EXTENSION: 20" SOLUBILITY IN WATER: 0% SPECIFIC GRAVITY: 0.775 % VOLATILE BY VOLUME: 100% pH: N/A PROPELLANT: Carbon Dioxide EVAPORATION RATE: Fast BIODEGRADABILITY: No

LABEL INFORMATION

FIFTY NIFTY PARTS CLEANER AND DEGREASER

An ultra-fast drying, no residue, cleaning solvent intended to degrease any non-painted metal surface. This heavy duty cleaning agent instantly removes oil, dirt build-up, varnish, sludge, grease and brake fluid. Contains no chlorinated solvents and is 50 state compliant. The powerful spray breaks through even the toughest deposits!

DIRECTIONS: SHAKE WELL BEFORE USING. For best results, spray directly onto soiled surfaces. Allow foam to remain on the surface for five minutes then flush with water or wipe clean. For heavy build-up allow to remain on the surface for several minutes prior to flushing or wiping. For thick encrusted build-up a stiff bristle brush may be required.

NOTE: This product will attack painted surfaces, rubber and plastic. Flush with water immediately.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

CONTAINS (CAS#): Acetone (67-64-1), Carbon Dioxide (124-38-9), Heptane (142-82-5), C8-9 Alkane/Cycloalkane (64742-49-0), C6-9 Light Alkanes (68410-97-9).



PACKAGING INFORMATION

12 - 20 oz. cans per case, 14 oz. net weight.