

QuestSpecialty

Purity

Food Grade Lubricant & Protectant

Purity

Food Grade Lubricant & Protectant

Lubricante & Protector de Grado de Alimentos

Non-Toxic

Odorless & Tasteless

Contains No Silicone

DANGER/PELIGRO

EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. AEROSOL EXTREMADAMENTE INFLAMABLE. CONTIENE GAS A PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA.

NET WT. 16 OZ. (454 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
713.896.8188

NSF

Nonfood Compounds
H1
148100

A lubricant made up of USP liquid petrolatum and propellant, providing a sanitary means of lubricating dairy and food processing equipment. Resists water washout and has an operating range of 0°F to 300°F. Complies with FDA regulations, CFR Title 21, paragraphs 172.878 and 178.3620.

USED ON: Slides, bearings, pistons and rings, seals and pump parts, belts, etc.

USED IN: Fast Service Food Preparation, Cut Meat Cold Room Packaging in Supermarkets, Packaged Meat Units for Franchise Outlets, Ice Cream Filling Equipment, Milk Bottle Equipment.

DIRECTIONS: Spray 8-10 inches from surface to be lubricated. Leaves a pure food grade oil film. Reapply periodically.

INSTRUCCIONES: Rocíe 8-10 pulgadas de la superficie que va a ser lubricada. Deja una capa pura de aceite de grado de alimento. Vuelva a aplicar periódicamente.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do

not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.




PELIGRO: Aerosol Extremadamente Inflamable. Contiene gas a presión; Puede explotar si se calienta.

Mantenga lejos de calor, chispas, llamas abiertas, y superficies calientes. -No fumar. No pulverice en llamas abiertas u otra fuente de ignición. Envase presurizado: No perforo ni quemé, incluso después de usar. Proteja de la luz solar. No exponga a temperaturas que excedan 50°C/122°F. Almacene en un lugar bien-ventilada.

CONTAINS (CAS#): White Mineral Oil (8042-47-5), Liquefied Petroleum Gas (64876-86-8).

Made in USA

Table with 2 columns: Hazard Category and Rating. Rows: HEALTH (1), FLAMMABILITY (3), REACTIVITY (0), PERSONAL (A).



ITEM 5400

60005540

60005540