

QuestSpecialty

Mr. Green

High Performance
Extreme Condition Grease

Mr. Green

High Performance Extreme Condition Grease

Grasa de Alto Rendimiento para
Condiciones Extremas

Calcium Sulfonate Grease with
Oxidation Inhibitors & Extreme Pressure
Additives for Severe Applications

Protects Surfaces Against
Corrosion and Resulting Seizing
From Fresh or Salt Water

Suitable for High Speed Bearings &
Centralized Lubrication Systems

Temperature Range of -20° to 500°F
Outstanding Film Strength

CAUTION/PRECAUCIÓN:
KEEP OUT OF REACH OF CHILDREN
SEE ADDITIONAL CAUTIONS ON BACK PANEL
NO SE DEJE AL ALCANCE DE LOS NIÑOS
VEA PRECAUCIONES ADICIONALES EN EL PANEL TRASERO

NET CONTENTS: 14 OZ. (397 g)

QuestSpecialty Corporation
PO Box 624 • Brenham, TX 77834 • 713.896.8188

MR. GREEN is recommended for severe applications in many industries. It is particularly suitable for high speed bearings and centralized lubrication systems. MR. GREEN is recommended for use in automotive as well as extreme pressure applications. MR. GREEN is suitable anywhere where shear stable, high load carrying, corrosion resistant grease is required. Forms protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This waterproof lubricant will not wash out. Resistant to corrosive salt water environments.

USES: Ball bearings, roller bearings, couplings, mechanical linkages, pumps, universal joints, ball joints, fifth wheels, construction, mining, agricultural, logging and hauling industries.

DIRECTIONS FOR USE: Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings: Fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

MODO DE EMPLEO: Inyecte grasa nueva hasta que la grasa vieja salga. Remueva la grasa vieja si es posible. Para conexiones de tipo bola: Llene hasta que la grasa vieja salga. Limpie las áreas expuestas con desengrasante para remover la grasa vieja. Inyecte nueva grasa.

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

PRECAUCIÓN: No se deje al alcance de los niños. Puede causar irritación a los ojos. El contacto prolongado puede causar irritación de la piel. Si es ingerido, puede causar náusea, vómito y diarrea. Si hay contacto con los ojos, enjuague con agua, vea a un médico si la sensación aceitosa persiste. Si hay contacto con la piel, lave con agua y jabón. Para la ingestión de más de 8 onzas contacte al médico.

CONTAINS (CAS#): Naphthenic Oil (64742-53-5), Calcium Sulfonate Complex (N/A).

NLGI GRADE: 2

HMS Ratings: Health - 1, Flammability - 1, Reactivity - 0, Personal - A.

Made in USA
60005051



ITEM L10400001-145G