

## GENERAL PURPOSE AEROSOL LUBRICANTS:

- 5210 - MC-FREE Methylene Chloride Free Dry Film Lube**
- Temperature Range -40°F to +662°F
  - Non-Chlorinated, Non-Corrosive, Non-Conductive
  - Adheres to Metal, Glass, Rubber & Most Plastics
  - Resists Pressures Up to 250,000 psi

- 5310 - KOPPER LUBE Copper-Based Anti-Seize**
- Temperature Range -20°F to +1800°F
  - Use Where Metal Contacts Metal
  - Allows Ground Conductivity
  - 50 State VOC Compliant
  - No Chlorinated or Fluorinated Solvents

- 5340/\*5350 - MR. MECHANIC Lubricant**
- Convenience Use on Small Parts and for Spot Applications
  - Eliminates Waste Due to Drips & Spills
  - A Four-In-One Product - Lubricates, Penetrates, Displaces Moisture, Prevents Corrosion

- 5370 - SILI LUBE Heavy Duty Silicone Spray**
- Reduces Metal-to-Metal Noises and Rubber-to-Metal Squeaks
  - Clean, Non-Staining Formula
  - Waterproof and Rustproof
  - Non-Flammable
  - Clean, Dry Spray Does Not Leave a Sticky Residue Behind
  - Non-Conductive to 28,000 Volts

- 5420 - GEAR LUBE EF Open Gear Lubricant**
- Heavy Service Temperature Range +20°F to +175°F
  - High Viscosity Formula Clings to Vertical & Overhead Surfaces & Won't Drip or Run

• Extends Life of Machinery & Equipment While Reducing Noise Output

- 5440 - MOLI-GUARD Lubricant Spray**

• Effective at Temperatures Up to 600°F & Under High Pressure Loads

- Quick Drying, Non-Tacky Finish Adheres Well to All Metals, Most Plastics, Glass & Rubber

• Molybdenum Disulfide Replaces Graphite to Free Frozen Surfaces, Stop Galling & Seizing of Metals and Prevent Chattering, Extending the Life of Machinery and Equipment

• Provides a Protective Barrier that Resists Dust and Abrasive Particles & Withstands Water, Oils, Alkalis & Most Acids

- 5460 - SURRENDER Anti-Seize**

- Prevents Metal-to-Metal Scraping
- Non-Chlorinated
- Non-Gumming Base with No Dropping Point
- Temperature Range from -20°F to 750°F

- 5660 - MICRO-DRY PTFE Dry Lubricant & Release Agent**

- Colorless, Stainless, Low Odor Formula with No Hexane
- Wide Temperature Range
- Excellent Release Agent
- Slicker than Silicone or Graphite Lubricants
- Temperature Range from -100°F to 500°F



## 5760 - NUCHAIN Chain and Cable Lubricant

- Prolongs Life of Chains, Cables & Wire Ropes
- Will Not Attract Dust & Dirt
- Protects Against Galling, Seizing & Wear
- Prolonged Use Reduces Chain Whip, Vibration & Noise

## LIQUID LUBRICANTS:

- 6000 - MR. MECHANIC**

- Loosens Dirt and Scale
- USDA Authorized
- Greaseless Light Duty Lubricant for General Use
- Four Way Protection - Lubricates, Penetrates, Displaces Moisture, Prevents Corrosion

- 6002 - MOLI-GUARD Dry Film Lubricant**

- Temperature Range -40°F To +600°F
- Reduces Friction - Retards Wear
- Adheres to Metal, Glass, Rubber & Most Plastics
- Resists Pressures up to 250,000 PSI
- Molybdenum Disulfide Replaces Graphite to Free Frozen Surfaces, Stop Galling and Seizing of Metals and Prevent Chattering
- Extends the Life of Machinery & Equipment

- 6004 - PIERCE Penetrating Oil**

- Provides a Protective Barrier that Resists Dust & Abrasive Particles & Withstands Water, Oils, Alkalis and Most Acids
- Loosens Rusted Nuts & Bolts
- Displaces & Seals Out Moisture
- Dielectric Strength to 29,000 Volts
- Protects Against Rust
- Improves Electrical Properties

• Authorized by USDA For Use In

Federally Inspected Meat & Poultry Plants

- 6005 - MC-FREE Methylene Chloride Free Dry Film Lubricant**
- Temperature Range -40°F to +662°F
  - Non-Chlorinated
  - Adheres to Metal, Glass, Rubber and Most Plastics
  - Resists Pressures up to 250,000 psi
  - Non-Corrosive, Non-Conductive
  - Resists Water Wash-out, Oils, Alkalis and Most Acids

- 6007 - LOOSE SCREW 4-in-1 Lubricating & Penetrating Oil**
- Non-Flammable
  - Displaces Moisture
  - Contains PTFE to Increase Lubricity
  - Inhibits Rust & Corrosion

## FOOD GRADE LUBRICANTS:

- 5280 - PEN EASE Food Grade Penetrating Oil**
- Light, Clean, Quick Penetrant
  - Excellent Rust Preventative
  - Long-Lasting Lubrication
  - Speeds Up Disassembly & Retooling
  - Food-Processing Friendly
  - Meets NSF H-1 Standards

- 5380 - SLIDE OUT Dry Silicone Spray**

- Concentrated... Goes a Long Way!
- Meets NSF H-1 Standards
- Reduces Friction Between Moving Parts, Even for Metal-to-Metal Contact Surfaces, Making Parts Last Longer

- 5400 - PURITY Food Grade Lubricant & Protectant**

- Non-Toxic
- Odorless & Tasteless
- Contains No Silicone
- Meets NSF H-1 Standards

- 5770 - EZ LUBE Food Grade White Grease**

- Lubricates, Reducing Friction & Wear
- High Viscosity, Clings to Vertical Surfaces
- Resists Extreme Pressure, Corrosion & Water Washout
- Wide Temperature Range of -40° - 550°F
- Resists Throw-Off, Excellent Adhesion Properties
- Meets NSF H-1 Standards
- White Color for Easy Visual Check

- 6220 - PURITY Food Grade Lubricant & Protectant**

- 100% Biodegradable & Odorless
- Petroleum White Mineral Oil
- One Step Application
- Meets NSF H-1 Standards
- Meets 21 CFR 172.878, 178.3620, 573.680

- L108 - EZ LUBE Food Grade White Grease**

- Lubricates
- Reduces Friction & Wear
- Meets NSF H-1 Standards
- Calcium Sulfonate Based
- Resists Extreme Pressure, Corrosion, Water Washout & Throw-Off
- Temperature Range of -40° - 500°F
- NLGI Grade 2
- Available in Aerosol (5770) & Bulk

## PENETRANTS:

- 5300 - LOOSE SCREW 4-in-1 Lubricant & Penetrating Oil**
- Non-Flammable
  - Displaces Moisture

• Contains PTFE to Inhibit Rust & Corrosion

• Meets Military Specifications MIL-C-23411 for Corrosion Prevention

- 5320 - GENESIS Penetrating Lubricant**

- Non-Flammable, Non-Conductive & Non-Chlorinated
- Prevents Rust & Displaces Moisture
- Four Way Protection

• Private Label Only



Scan QR Code to Check Out  
All Products, Tech Sheets &  
SDS's on Our Website!



P.O. Box 624  
Brenham, TX 77834  
713.896.8188  
www.questspecialty.com



P.O. Box 624  
Brenham, TX 77834  
713.896.8188  
www.questspecialty.com

# LUBRICANTS and PENETRANTS

Scan QR Code to Check Out All Products, Tech Sheets & SDS's on Our Website!



## 5500/\*5090 - PIERCE Penetrating Lubricant

- Versatile Light Duty Formula Penetrates, Lubricates, Prevents Corrosion & Displaces Moisture
- Silicone Free Formula Will Not Interfere with Subsequent Painting
- Non-Flammable
- Meets Mil Spec C-2344

## 5510 - OUTBREAK Cherry Penetrating Lubricant

- Rapid Penetrating Action Breaks Free Rusted Bolts
  - JQ Technology Quickly Breaks & Blasts Away Rust
  - 50 State VOC compliant
  - Non-flammable
  - Quickly Breaks Down Corrosion
  - Displaces moisture
- ## 5690 - RUST RELEASE Foaming Penetrating & Cutting Oil
- Reduces Metal-to-Metal Noise
  - Prolongs Tool Life
  - Resists Rust and Corrosion Even in Extreme Conditions

## 5740 - SLICK Lubricant

- Contains PTFE and Moly for Excellent Lubrication
- Prolongs Life of Machinery
- Withstands Heavy Loads
- Resists Rust and Corrosion Even in Extreme Conditions

## 5810 - ULTRA TAC High Pressure, Penetrating Lubricant

- Quickly Penetrates Rust, Corrosion & Soil
- Sets Up as a Viscous, High Impact Grease, Adding Protection & Heavy Lubrication
- Excellent Lubricant for Gears, Chains, Slides & Turning Parts
- Leaves a Protective PTFE Coating to Protect Tools & Machinery

## 5970 - CHILL OUT Freezing Penetrating Oil

- Freezing Action Unlocks Rusted Parts
- Low VOC Content
- Non-Conductive & Non-Chlorinated

## GREASES:

### 5720 - BODACIOUS High Pressure, Non-Melt, Red Grease

- High Shock & Impact Resistance
- Prolongs Life of Metal Parts
- Contains Corrosion and Rust Inhibitors
- Exceptional Adhesive Cohesive and Anti-Wear Properties

## 5750 - BIG RED Non-Melt Spray Grease

- Waterproof & Prevents Corrosion
- Forms Thick, Long-Lasting Film
- Provides Superior Lubrication
- Accepts High Pressure
- 0°F – 350°F Temperature Range
- 50 State VOC Compliant

- Red Color Provides Easy Visual Inspection
- Prevents Rust—Extends Life of Equipment

## 5830 - SAFE BET Penetrating, Multi-Purpose Grease

- Lithium Complex Formula
- Methylene Chloride Free
- Lubricant, Penetrant & Rust Preventative
- Sprays on Like an Oil & Sets Up to a Tough Grease in Minutes
- 50 State VOC Compliant
- Temperature Range 0°F to 350°F

## L102 - MOLY TUFF Non-Melt, Black Grease

- Stays Put Longer than Other Greases
- NLGI Grade 2
- Temperature Range -20° to 500°F
- Extreme Pressure Additives
- Resists Corrosion and Resulting Seizing of Fittings
- Resists Acids, Salt Spray, Water, Weather, Dirt & Oxidation
- Earned GC-LB Classification by National Lubricating Grease Institute

## L103 - BIG RED Non-Melt, High Polymer Red Grease

- Extreme Pressure Additives for High Loads
- NLGI Grade 3
- Stays Put Longer than Other Greases
- Temperature Range 0°-300°F
- Resists Corrosion & Resulting Seizing of Fittings
- Resists Acids, Salt Spray, Water, Weather, Dirt & Oxidation

## L104 - MR. GREEN Lithium E.P. Green Grease

- Oxidation Inhibitors for a Wide Range of Uses
- Protects Surfaces Against Corrosion and Resulting Seizing from Fresh or Salt Water
- Extreme Pressure Additives for High Loads
- Easy to Use Cartridges for Use in Hand Grease Applicators
- Temperature Range of -20° to 500°F
- NLGI Grade 2

## L106 - BIG GREEN Super Impact Non-Melt E.P. Grease

- High Shock & Impact Resistance
- All Weather Performance
- Bentonite Based Formula with Wide Temperature Range
- Extreme Pressure Additives for High Loads
- Unique Rust & Corrosion Inhibitors
- Resists: Acids, Water, Salt Spray, Dust & Dirt
- Temperature Range of 0° to 300°F
- NLGI Grade 3

## L107 - MR. JOE Amber Premium Lithium E.P. Grease

- Resists Thinning or Hardening in Medium Sized High Speed Bearings
- Lithium Grease with Oxidation Inhibitors & Extreme Pressure Additives for Wide Range of Uses
- Protects Surfaces Against Corrosion
- Operating Range of 0°F to +350°F
- NLGI Grade 2

## L150 - HYDRAULIC OIL 10W40 High Performance Multi-Viscosity Hydraulic Oil

- For Hydraulic Systems and Compressors
- Provides Long Performance Life
- Contains Demulsifier and Anti-Leak Additives

## L160 - RED UNIVERSAL GEAR OIL 80W90 High Performance Super Gear Oil

- Anti-Wear, Anti-Foaming & Extreme Pressure Characteristics
- Enhanced Thermal and Oxidation Stability
- During Wide Operating Temperatures
- Superior Corrosion Resistance to Ferrous and Non-Ferrous Parts
- Provides Longer Service Gear Life Even at High Speeds
- Excellent Resistance to Water & Demulsibility

## L180 - RED UNIVERSAL GEAR OIL 85W140 High Performance Super Gear Oil

- Outstanding Anti-Wear, Anti-Foaming & Extreme Pressure Characteristics
- Enhanced Thermal and Oxidation Stability
- During Wide Operating Temperatures
- Superior Corrosion Resistance to Ferrous and Non-Ferrous Parts
- Provides Longer Service Gear Life Even at High Speeds
- Excellent Resistance to Water & Demulsibility

## L1801 - GREEN UNIVERSAL GEAR OIL 85W140 High Performance Super Gear Oil

- Outstanding Anti-Wear, Anti-Foaming & Extreme Pressure Characteristics
- Enhanced Thermal and Oxidation Stability
- During Wide Operating Temperatures
- Superior Corrosion Resistance to Ferrous and Non-Ferrous Parts
- Provides Longer Service Gear Life Even at High Speeds
- Excellent Resistance to Water & Demulsibility

## L639 - SURRENDER Anti-Seize

- Prevents Galling, Seizing and Galvanic Action
- Long Term Protection Indoors or Outdoors with Just One Application
- Will Not Evaporate, Separate or Harden
- Temperature Range of -30°F to +2200°F
- NLGI Grade 2

## L660 - KOPPER LUBE Copper-Based Anti-Seize

- Allows Ground Conductivity
- Protects Against Rust, Corrosion & Oxidation
- Prevents Galling and Seizing at Metal Contact Points
- Temperature Range of 0°F to 350°F
- NLGI Grade 2
- Private Label Only

