

Safety Data Sheet
Carbon Off

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Carbon Off

PRODUCT CODE: 10101, 10102, 10632, 11216

RECOMMENDED USE: Carbon Remover

RESTRICTIONS ON USE: This product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

COMPANY NAME: QuestSpecialty Corporation

COMPANY ADDRESS: P.O. Box 624, Brenham, TX 77834

COMPANY PHONE: 800-231-0454

EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Skin Corrosive: Category 1B

Eye Damage: Category 1

Carcinogenicity: Category 2

Specific Target Organ Toxicity (Repeated Exposure): Category 2

Specific Target Organ Toxicity (Single Exposure): Category 3

Reproductive Toxicity: Category 2

Corrosive to Metals

HAZARD STATEMENT(S): DANGER: Causes severe skin burns and serious eye damage. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. May damage fertility or the unborn child. May cause respiratory irritation, drowsiness or dizziness. May be corrosive to metals.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Do not breathe fume, mists or vapors. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store in a well-ventilated place locked up. Keep container tightly closed. Dispose of contents and container in accordance with local, state, and national regulations. Keep only in original container. Absorb spillage to prevent material damage. Store in a corrosive resistant container with a resistant inner liner. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed, concerned, or feeling unwell: Get medical advice or attention.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
2-Butoxyethanol	127087-87-0	5-25%
Ammonium Hydroxide	1336-21-6	1-5%
Ethyl Alcohol	64-17-5	2-6%
Methanol	67-56-1	5-25%
Methylene Chloride	75-09-2	60-100%
Toluene	108-88-3	1-5%

Safety Data Sheet

Carbon Off

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION: If inhaled: Remove person to fresh air and keep comfortable for breathing.

SKIN: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

ACUTE HEALTH HAZARDS: Eyes: serious damage, redness, tearing, blurred vision

Skin: severe burns, defatting and dermatitis

Inhalation: Irritation

Oral: Aspiration risk, abdominal irritation, nausea, vomiting, and diarrhea

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, lungs, blood, reproductive or central nervous systems. May cause dizziness, headache, nausea, mental confusion, or visual disturbances.

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, and alcohol foam.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Phosgene, Hydrogen Chloride Gases & Nitrogen and Carbon oxides.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Remove any source of heat, flame, or sparks. Evacuate affected area. Mop up with appropriate absorbent material. Avoid breathing fumes ventilate area. Dispose of residue in accordance with federal, state and local guidelines.

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Use only outdoors or in a well-ventilated area. Store in a well-ventilated place locked up. Keep container tightly closed. Keep container tightly closed.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: May attack certain plastics, rubber, & coatings. Incompatible w/ strong oxidizers & caustics, chemically active metal, such as Aluminum, magnesium powder, sodium, potassium, and lithium.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
2-Butoxyethanol	50 ppm	20 ppm
Ammonium Hydroxide	50 ppm	25 ppm
Ethyl Alcohol	1000 ppm	1000 ppm
Methanol	200 ppm	200 ppm
Methylene Chloride	25 ppm	50 ppm
Toluene	200 ppm	50 ppm

ENGINEERING CONTROLS / VENTILATION: Ambient ventilation suitable, forced ventilation should not be required

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

Safety Data Sheet

Carbon Off

ADDITIONAL MEASURES: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Pale Yellow Liquid

ODOR: Ammonia odor

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: > 140°F (60°C)

FLASH POINT: N/D

EVAPORATION RATE: >2

FLAMMABILITY(solid/gas): Not considered a flammable liquid by OSHA (29CFR 1910.1200)

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

EXPLOSIVE LIMIT LOWER (%): N/D

EXPLOSIVE LIMIT UPPER (%): N/D

VAPOR PRESSURE (mm Hg): >100

VAPOR DENSITY (AIR=1): >2

RELATIVE DENSITY (H₂O=1): 1.17 @ 77°F (25°C)

SOLUBILITY(IES): 0%

PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D

AUTOIGNITION TEMPERATURE: N/D

DECOMPOSITION TEMPERATURE: N/D

VISCOSITY: 250cps

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: Chemically active metals and acids

CHEMICAL STABILITY: Stable

POSSIBLE HAZARDOUS REACTIONS: None Known

CONDITIONS TO AVOID: Excessive heat. Sources of ignition.

INCOMPATIBLE MATERIALS: May attack certain plastics, rubber, & coatings. Incompatible w/ strong oxidizers & caustics, chemically active metal, such as Aluminum, magnesium powder, sodium, potassium, and lithium.

HAZARDOUS DECOMPOSITION PRODUCTS: Phosgene, Hydrogen Chloride Gases, Nitrogen & Carbon oxides.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **Methylene Chloride** (75-09-2): LD₅₀ (Oral, Rat) >2000 mg/kg. LD₅₀ (Dermal Rat) >2000 mg/kg. LC₅₀ (Inhalation, Rat) 52000 mg/m³. **Toluene** (108-88-3) LD₅₀ (Oral, Rat) 5580 mg/kg; LD₅₀ (Dermal, Rabbit) > 5000 mg/kg; LC₅₀ (Inhalation, Rat, 4hrs) 28.1 mg/L **Ammonium Hydroxide** (1336-21-6) LD₅₀ (Oral, Rat) 350 mg/kg **2-Butoxyethanol** (111-76-2) LD₅₀ (Oral, Rat) 320 mg/kg; LC₅₀ (Inhalation, Mice, 4hr) 700 ppm; LD₅₀ (Dermal, Rabbit) 440 mg/kg **Ethyl Alcohol** (64-17-5) LC₅₀ (Inhalation, Rat, 4hr) 133.6 mg/L; LD₅₀ (Oral, Rat) >8311 mg/kg; LD₅₀ (Dermal, Rabbit) 16972.5 mg/kg **Methanol** (67-56-1) Oral LD₅₀ (Rat) 1187-2769 mg/kg; Inhalation LC₅₀ (Rat, 4h) 128.2 mg/l

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes irritation, redness, temporary eye damage.

INGESTION: Causes gastrointestinal irritation, nausea, vomiting, abdominal cramps, dizziness.

INHALATION: May cause irritation to the respiratory tract, headaches, nausea, vomiting, lungs, and may cause fatigue. Excessive or prolonged exposure may cause dizziness and unconsciousness.

SKIN: Causes mild irritation, dryness, localize defatting.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.

ACUTE HEALTH HAZARDS: Eyes: serious damage, redness, tearing, blurred vision

Skin: severe burns, defatting and dermatitis

Inhalation: Irritation

Oral: Aspiration risk, abdominal irritation, nausea, vomiting, and diarrhea

Safety Data Sheet

Carbon Off

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, lungs, blood, reproductive or central nervous systems. May cause dizziness, headache, nausea, mental confusion, or visual disturbances.

CARCINOGENICITY: OSHA: Yes ACGIH: A2 - Suspected NTP: 1 - Known Carcinogen IARC: 1 - Human OTHER: CA Prop 65

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: Not Established

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATIVE POTENTIAL: Components in this mixture can bioaccumulate in aquatic organisms.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: This material is toxic to aquatic life.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: For Containers 1.3 Gallons (5 liters) and smaller: Cleaning Compound N.O.S

For Containers Larger than 1.3 Gallons (5 liters): Dichloromethane Mixture

HAZARD CLASS/DIVISION: 6.1

UN/NA NUMBER: UN 1593

PACKING GROUP: III

AIR SHIPMENT

PROPER SHIPPING NAME: Dichloromethane Mixture

HAZARD CLASS/DIVISION: 6.1

UN/NA NUMBER: UN 1593

PACKING GROUP: III

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Dichloromethane Mixture

HAZARD CLASS/DIVISION: 6.1

UN/NA NUMBER: UN 1593

PACKING GROUP: III

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): **Methanol** (67-56-1) Reportable Quantity = 5,000 lbs **Methylene Chloride** (75-09-2) Reportable Quantity = 1,000 lbs **Toluene** (108-88-3) Reportable Quantity = 1,000 lbs **Ammonium Hydroxide** (1336-21-6) Reportable Quantity = 1,000 lbs

SARA 311/312 HAZARD CATEGORIES: Acute Health, Chronic Health.

SARA 313 REPORTABLE INGREDIENTS: 2-Butoxy ethanol - 111-76-2, Methyl alcohol - 67-56-1, Methylene chloride - 75-09-2, Toluene - 108-88-3, Ammonium hydroxide - 1336-21-6

STATE REGULATIONS: **CA Prop 65:** This product contains chemicals known to the state of California to cause cancer: **Methylene Chloride** (75-09-2) **RTK:** MA, NJ, PA This product contains chemicals known to the state of California to cause reproductive and/or developmental toxicity: **Methanol** (67-56-1) and **Toluene** (108-88-3)

INTERNATIONAL REGULATIONS: Methylene Chloride - 75-09-2 - The components of this product are listed on the chemical inventories of the following countries: Australia - Hazchem. code 2Z, Poison Schedule S5, China, Europe (EINECS), Japan, Korea, Philippines, Canada. **WHMIS (Canada):** Class D-1B material causing immediate and serious toxic effects (toxic). Class

Safety Data Sheet

Carbon Off

D-2A: Material causing other toxic effects (very toxic). **DSCL (EEC): R22** - Harmful if swallowed. R38-irritating to skin. R41- Risk of serious damage to eyes. R45- May cause cancer.

VOLATILE ORGANIC COMPOUNDS (VOC): 16.8%

This product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

NFPA HEALTH: 3

HMIS HEALTH: 3

NFPA FLAMMABILITY: 1

HMIS FLAMMABILITY: 1

NFPA REACTIVITY: 0

HMIS REACTIVITY: 0

NFPA OTHER: None

HMIS PROTECTION: B

7.25 # Methylene Chloride per gallon

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Andrew Bach

DATE PREPARED: 1/27/2014

REVISION DATE: 05/23/2019

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.