SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Mister Blister
PRODUCT CODE: 6090
RECOMMENDED USE: Paint and Varnish Remover
RESTRICTIONS ON USE: None known.
COMPANY NAME: QuestSpecialty Corporation
COMPANY ADDRESS: P.O. Box 624, Brenham, TX 77834
COMPANY PHONE: 800-231-0454
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable liquid: Category 2

Skin corrosion/irritation: Category 1

Specific Target Organ Toxicity (Single Exposure): Category 3

Specific Target Organ Toxicity (Repeated Exposure): Category 2

Reproductive Toxicity: Category 2

HAZARD STATEMENT(S): DANGER: Highly flammable liquid and vapor. Causes severe skin burns and eye damage. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tool. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water (or shower). In case of fire: Use alcohol resistant foam, Carbon dioxide, or dry powder to extinguish. Do not breathe dust, fume, mist, vapor or spray. Wash hands with soap and water thoroughly after handling. Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Take off Immediately all contaminated clothing. Immediately rinse with water for several minutes. IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately. Specific treatment (see First Aid Measures section of this SDS). Use only outdoors or in a well-ventilated place. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Obtain, read, and follow all safety instructions before use. If exposed or concerned, get medical advice. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

| SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS | | | | | |
|--|------------|---------|--|--|--|
| HAZARDOUS INGREDIENT | CAS NUMBER | PERCENT | | | |
| Acetone | 67-64-1 | 35-45% | | | |
| 1,3-Dioxolane | 646-06-0 | 25-35% | | | |
| Monoethanolamine | 141-43-5 | 1-5% | | | |
| Isopropylidene glycol | 100-79-8 | 1-5% | | | |
| | | | | | |

SECTION IV - FIRST AID MEASURES

- **EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
- **INGESTION**: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention if irritation persists.

Safety Data Sheet

Mister Blister

- **INHALATION**: Move to fresh air. If breathing is difficult, administer oxygen. If heartbeat or breathing seem irregular, seek immediate medical attention.
- **SKIN:** Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.
- ACUTE HEALTH HAZARDS: Causes severe skin burns and eye damage. Inhalation of vapors may cause nausea, dizziness and drowsiness.
- **CHRONIC HEALTH HAZARDS:** Causes damage to organs through prolonged and repeated exposure. May cause reproductive effects affecting fertility and/or development of the unborn child.
- **NOTE TO PHYSICIAN:** There is no specific treatment regimen. Treatment of overexposure should be directed toward the control of symptoms and the clinical condition of the patient.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam or carbon dioxide.

UNSUITABLE EXTINGUISHING MEDIA: Water jets or streams may spread fire.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS: HIGHLY FLAMMABLE. Keep away from heat, sparks, open flames and other sources of ignition.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Contain spill, eliminate ignition sources and ventilate area. Prevent spill from entering sewers, storm drains, and natural waterways. Use non-combustible material like vermiculite, sand or earth for larger spills.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Store in a cool, dry area. Keep away heat, open flames, or other sources of ignition. Do not reuse empty container. Keep out of reach of children.

OTHER PRECAUTIONS: Keep out of the reach of children. Follow label directions exactly. Avoid contact with eyes, skin or clothing. **INCOMPATIBILITY:** Strong acids.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

| HAZARDOUS INGREDIENT | OSHA PEL | ACGIH TLV |
|-----------------------|-----------------|-----------------|
| Acetone | 1000 ppm | 500 ppm |
| 1,3-Dioxolane | Not Established | 20 ppm |
| Monoethanolamine | 3 ppm | 3 ppm |
| Isopropylidene glycol | Not Established | Not Established |

ENGINEERING CONTROLS / VENTILATION: Local ventilation/exhaust adequate to maintain vapor concentrations below PEL/TLV.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded. **PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses/goggles and chemical resistant gloves.

ADDITIONAL MEASURES: Avoid contact with skin, eyes or clothing. Do not touch eyes when using this product. Wash hands thoroughly with soap and water after use. Take off contaminated clothing and wash it before reuse. Avoid breathing spray.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Blud Green Spray. ODOR: Acetone odor. ODOR THRESHOLD: N/D pH: N/A

MELTING POINT/FREEZING POINT: N/D INITIAL BOILING POINT AND BOILING RANGE: N/D FLASH POINT: N/D EVAPORATION RATE: N/D FLAMMABILITY (solid/gas): Highly Flammable liquid. **UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:** LOWER FLAMMABILITY LIMIT: N/D UPPER FLAMMABILITY LIMIT: N/D EXPLOSIVE LIMIT LOWER (%): N/D EXPLOSIVE LIMIT UPPER (%): N/D VAPOR PRESSURE (mm Hg): N/D VAPOR DENSITY (AIR=1): N/D **RELATIVE DENSITY (H2O=1):** 0.95 - 0.98 SOLUBILITY(IES): Miscible. PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D **AUTOIGNITION TEMPERATURE: N/D** DECOMPOSITION TEMPERATURE: N/D VISCOSITY: 1000 - 1500 cps

SECTION X - STABILITY AND REACTIVITY

REACTIVITY: Chemically active metals and acids. CHEMICAL STABILITY: Stable. POSSIBLE HAZARDOUS REACTIONS: None known. CONDITIONS TO AVOID: Avoid incompatible materials. INCOMPATIBLE MATERIALS: Strong acids. HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

SECTION XI – TOXICOLOGICAL INFORMATION

 $\begin{array}{l} \textbf{TOXICOLOGICAL INFORMATION: Acetone (67-64-1): LD_{50} (Oral, Rat) 5800 mg/kg; LD_{50} (Oral, Mouse) 3000 mg/kg; LD_{50} (Oral, Rabbit) 5340 mg/kg; LC_{50} (Inhalation, Rat, 8h) 50100 mg/m^3; LC_{50} (Inhalation, Mouse, 4h) 44,000 mg/m^3. \\ \textbf{Monoethanolamine (141-43-5): LD_{50} (Oral, Rat) 1720 mg/kg; LD_{50} (Dermal, Rabbit) 1025 mg/kg; LC_{50}. \\ \textbf{Isopropylidene glycol (100-79-8): LD_{50} (Oral, Rat) 7000 mg/kg; LD_{50} (Dermal, Rat) 2000 mg/kg; LC_{50} (Inhalation, Rat, 4h aerosol) >5.11 mg/L. \\ \end{array}$

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes serious eye damage.

INGESTION: Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomitting, abdominal cramps.

INHALATION: Causes dizziness, headaches, nausea.

SKIN: Causes irritation.

MEDICAL CONDITION AGGRAVATED: May aggravate pre-existing conditions of the liver, kidneys, and skin.

ACUTE HEALTH HAZARDS: Causes severe skin burns and eye damage. Inhalation of vapors may cause nausea, dizziness and drowsiness.

CHRONIC HEALTH HAZARDS: Causes damage to organs through prolonged and repeated exposure. May cause reproductive effects affecting fertility and/or development of the unborn child.

CARCINOGENICITY: OSHA: Not classified. ACGIH: No NTP: No IARC: No OTHER: No

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: Acetone (67-64-1): LC₅₀ (*Oncorhynchus mykiss*, 96h) 5540 mg/L; EC₅₀ (*Daphnia magna*, 48h) 6100 mg/L; EC₅₀ (*Selenastrum quadricauda*, 8d) 7500 mg/L; EC₅₀ (*Psuedomonas putida*, 16h) 1700 mg/L.

PERSISTENCE AND DEGRADABILITY: N/D BIOACCUMULATIVE POTENTIAL: N/D MOBILITY IN SOIL: N/D

OTHER ADVERSE EFFECTS: Avoid release to the environment.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

 PROPER SHIPPING NAME:
 For Quarts: Cleaning Compound, N.O.S. For packaging in Gallons or larger: Flammable Liquid, N.O.S.

 (Acetone, Dioxolane).
 HAZARD CLASS/DIVISION: 3

 UN/NA NUMBER:
 UN1993

 PACKING GROUP:
 II

 AIR SHIPMENT
 PROPER SHIPPING NAME:

 For Quarts: Cleaning Compound, N.O.S. For packaging in Gallons or larger: Flammable Liquid, N.O.S.

 (Acetone, Dioxolane).

 HAZARD CLASS/DIVISION: 3

HAZARD CLASS/DIVISION: 5UN/NA NUMBER:UN1993PACKING GROUP:II

 SHIPPING BY WATER:

 VESSEL (IMO/IMDG)

 PROPER SHIPPING NAME:
 For Quarts: Cleaning Compound, N.O.S. For packaging in Gallons or larger: Flammable Liquid, N.O.S.

 (Acetone, Dioxolane).
 HAZARD CLASS/DIVISION: 3

 UN/NA NUMBER:
 UN1993

 PACKING GROUP:
 II

 ENVIRONMENTAL HAZARDS WATER:
 N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Acetone (67-64-1) Reportable Quantity = 5,000 pounds.

SARA 311/312 HAZARD CATEGORIES: Acute Health, Chronic Health, Fire, Pressure.

SARA 313 REPORTABLE INGREDIENTS: Acetone (67-64-1).

STATE REGULATIONS: California Proposition 65: WARNING: This product can expose you to chemicals including Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Acetone (67-64-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, PA, RI, WA. 1,3-Dioxolane (646-06-0): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: MA, MN, NJ, PA, RI, WA. 1,3-Dioxolane (646-06-0): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: MA, MN, NJ, PA. Dimethyl carbonate (616-38-6): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: MA, PA. Methanol (67-56-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: MA, PA. Methanol (67-56-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: MA, PA. Methanol (67-56-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, IL, ME, MA, NJ, NY, NC, PA, RI, WA.

INTERNATIONAL REGULATIONS: Components are listed or exempted including Australia, Korea, United Kingdom, and Canada. **VOLATILE ORGANIC COMPOUNDS (VOC):** 42%

| | • | | |
|--------------------|------|-------------------------|---|
| NFPA HEALTH: | 3 | HMIS HEALTH: 3 | ; |
| NFPA FLAMMABILITY: | 3 | HMIS FLAMMABILITY: | 3 |
| NFPA REACTIVITY: | 0 | HMIS REACTIVITY: | 0 |
| NFPA OTHER: | None | HMIS PROTECTION: | В |
| | | | |

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Craig Bernard **DATE PREPARED:** 08/01/2019 **REVISION DATE:** 11/01/2023

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are

described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.