

SILI LUBE

HEAVY DUTY SILICONE SPRAY



DESCRIPTION

SILI LUBE is a multi-purpose silicone spray. Non-flammable formula is safe to use in plant areas. Formula uses a high viscosity silicone for long lasting lubrication and protection. Non-conductive to 28,000 volts. Stable temperatures up to 400°F.

APPLICATIONS

Cleans, shines and leaves a protective film on rusted parts, wire cable, door hinges, chains, hoists, pulleys, cranes, fork lifts, sprockets, gears, block and tackle, conveyors, construction machinery, industrial parts and locks. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

FEATURES & BENEFITS

- Reduces metal-to-metal noises and rubber-to-metal squeaks
- Clean, non-staining formula
- Waterproof and rustproof
- Non-flammable

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 25 ppm OSHA TLV
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: None
FLAME EXTENSION: None
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.46
% VOLATILE BY VOLUME: 95%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Slow
BIODEGRADABILITY: No

LABEL INFORMATION

SILI LUBE SILICONE SPRAY

Stops sticking of drawers, windows, doors, screens, zippers and locks. Eliminates annoying squeaks in hinges, latches and springs, etc. Stops car doors, locks and trunk moldings from sticking.

Retards corrosion – protects battery terminals, tools, guns, skates, aluminum windows and doors, etc. Waterproofs ignition systems and sparkplugs. Prevents jamming and production slow down. Contains no animal or vegetable fats. Absolutely neutral. This formulation has been authorized for use in federally inspected meat and poultry plants by the USDA.

DIRECTIONS: Thoroughly clean the surface to be sprayed. Spray a light film with a sweep motion. When used on sticking surfaces, work object back and forth. Spray again if necessary. **NOTE:** Product may harm some plastics TEST before using.


DANGER: Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause cancer. May cause drowsiness and dizziness. Suspected of causing genetic defects. May cause an allergic skin reaction.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves, eye protection, and protective clothing. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. Contaminated work clothing must not be allowed out of the workplace. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing dust/fumes/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Dispose of contents and container in accordance with local, state, and national regulations.

WARNING: This product can expose you to chemicals including Trichloroethylene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Trichloroethylene (79-01-6), Tetrachloroethylene (127-18-4), Polysiloxane (63148-62-9), Carbon Dioxide (124-38-9).

HEALTH	2
FLAMMABILITY	0
REACTIVITY	1
PERSONAL	C



PACKAGING INFORMATION

12 – 16 oz. cans per case, 15 oz. net weight