

BREACH

SUPER PENETRANT



DESCRIPTION

BREACH is a penetrating lubricant that loosens fasteners or bolts that are stuck or frozen in place so they can be removed or separated. **BREACH** seeps into crevices or small spaces between threaded parts to release them. **BREACH** can displace moisture and prevent corrosion between fasteners.

APPLICATIONS

For use in machine shops, factories, assembly plants, electronics repair shops, air conditioning repair, auto body shops, locksmiths, auto mechanic shops, oil rigs.

FEATURES & BENEFITS

- Breaks up rust
- Quickly loosens frozen bolts
- Displaces moisture
- Lubricating Action

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Mild
COLOR: Colorless
DETERGENCY: None
TOXICITY: 200 mg/m3 ACGIH TLV
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year+
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/D
FLAME EXTENSION: None
SOLUBILITY IN WATER: Insoluble.
SPECIFIC GRAVITY: .84
VOC: 16.5%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Slow
BIODEGRADABILITY: No

LABEL INFORMATION

BREACH SUPER PENETRANT

A penetrating lubricant that loosens fasteners or bolts that are stuck or frozen in place so they can be removed or separated. **BREACH** seeps into crevices or small spaces between threaded parts to release them. **BREACH** can displace moisture and prevent corrosion between fasteners.


USES: For use in machine shops, factories, assembly plants, electronics repair shops, air conditioning repair, auto body shops, locksmiths, auto mechanic shops, oil rigs.

DIRECTIONS: Spray liberally directly on area to be treated. Reapply periodically as required.

DANGER: Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. If swallowed: Immediately call a poison center or a doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state and federal regulations.

CONTAINS (CAS#): Distillates (petroleum), hydrotreated light (64742-47-8), Naphtha (petroleum), hydrotreated heavy (64742-48-9), Dipropylene glycol n-propyl ether (29911-27-1), Carbon dioxide (124-38-9), Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7).

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

12 – 16 oz. cans per case, 11 oz. net weight