

AVERT

CORROSION INHIBITOR



DESCRIPTION

AVERT will prevent rust and corrosion on all metal parts. Affords long term protection for indoor storage. Excellent for protecting materials while in transit. A 2 or 3 mil coating will provide protection for indoor storage for up to 2 years. Film is transparent, easy to see through. Can be removed by washing with kerosene or mineral spirits. Once removed, parts can be painted.

APPLICATIONS

Apply to machine parts, dies, pipe threads, casting, tools, jigs and stamped metal parts. Prevents corrosion due to salt spray on cables, hoists, pulleys, winches and riggings.

FEATURES & BENEFITS

- Non Drying Formula
- Long Term Rust Preventative Lubricant

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Oily
COLOR: Milky tan liquid
DETERGENCY: N/A
TOXICITY: 5000 ppm OSHA PEL
WETTING ABILITY: Good
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: N/A

FLASH POINT: N/A
FLAME EXTENSION: 15"
SOLUBILITY IN WATER: Non Soluble
SPECIFIC GRAVITY: 0.85
VOC: 15.2%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: No

LABEL INFORMATION

AVERT CORROSION INHIBITOR


This will prevent rust and corrosion on all metal parts. Apply to machine parts, dies, pipe threads, casting, tools, jigs and stamped metal parts. Prevents corrosion due to salt spray on cables, hoists, pulleys, winches and riggings. Affords long term protection for indoor storage. Excellent for protecting materials while in transit. A 2 or 3 mil coating will provide protection for indoor storage for up to 2 years. Film is transparent, easy to see through. Can be removed by washing with kerosene or mineral spirits. Once removed, parts can be painted.

DIRECTIONS FOR USE: Product is most effective when parts are clean and free of rust, scale or dirt. Remove protective cap. Point opening in spray tip towards part to be coated. Holding can 8 to 10 inches from part, spray 2 or 3 mil coat with a slow sweeping motion. Completely wet surface.

WARNING: Flammable aerosol. Contains gas under pressure; may explode if heated. Keep away from heat, sparks, open flames or hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

CONTAINS (CAS): Distillates (petroleum), hydrotreated light CAS 64742-47-8, Carbon Dioxide CAS 124-38-9.

| | |
|--------------|---|
| HEALTH | 1 |
| FLAMMABILITY | 2 |
| REACTIVITY | 0 |
| PERSONAL | B |



PACKAGING INFORMATION

12 – 16 oz cans per case, 11 oz net weight