

BLING IT ZINC

SHINY GALVANIZE COATING



DESCRIPTION

BLING IT ZINC is designed to protect iron and steel surfaces from rust and corrosion. Its high zinc content assures maximum protection on metal surfaces. Dries quickly to a hard film containing 93% zinc dust. Provides two way protection, first with the high zinc content protective coating, secondly with true galvanic action. Galvanic action is effective when surface is scratched, broken or dissipated and moisture is present. Easy to apply. Compares to a hot dip galvanize when applied as a 3 mil thickness. Formulated for use in presence of moisture, salts and acids. Meets ASTM A780 & D520.

APPLICATIONS

Areas of use include bus barns, refineries, pipe yards, oil rigs and industrial plants. For iron and steel surfaces, air conditioners, truck and auto fleets, automotive bodies, agriculture equipment, fences, metal roofs, metal buildings, metal fabricators, railroad equipment and marine equipment.

FEATURES & BENEFITS

- Will not crack, peel, or yellow even under extreme conditions
- 93% pure zinc after drying
- Provides excellent adhesion to all metal surfaces
- Dries to a flexible, paintable coating
- Coverage of 30 to 40 square feet per can at 1 mil thickness

SPECIFICATIONS

FORM: Solvent Based Aerosol	FLASH POINT: N/A
ODOR: Solvent	FLAME EXTENSION: 18"
COLOR: Silver	SOLUBILITY IN WATER: Moderate
DETERGENCY: None	SPECIFIC GRAVITY: 1.23
TOXICITY: 100 ppm OSHA PEL	% VOC: 58.9%
WETTING ABILITY: N/A	pH: N/A
STORAGE STABILITY: 1 Year	PROPELLANT: Hydrocarbon
COLD STABILITY: 32°F	EVAPORATION RATE: Fast
PHOSPHATES: None	BIODEGRADABILITY: No
TEMPERATURE TOLERANCE: Continuous 250°F Intermittent 300°F	

LABEL INFORMATION

BLING IT ZINC SHINY GALVANIZE COATING

This product is designed to protect iron and steel surfaces from rust and corrosion. Its high zinc content assures maximum protection on metal surfaces. Dries quickly to a hard film containing 93% zinc dust. Provides two way protection, first with the high zinc content protective coating, secondly with true galvanic action. Galvanic action is effective when surface is scratched, broken or dissipated and moisture is present. Easy to apply. Compares to a hot dip galvanize when applied as a 3 mil thickness. Formulated for use in presence of moisture, salts and acids. Meets ASTM A780.


DIRECTIONS: Shake can for a full 60 seconds after rattling of mixing ball begins. If application is to cover a large area, periodically shake can to insure uniform mixing of the contents. Surface to be sprayed should be clean and dry. Holding can 10-12 inches from the surface, apply in thin, even coats until surface is completely covered. Allow 5 to 10 minutes after application before handling. After spraying, turn can upside down and spray until no more zinc is evident. This product is best applied at room temperature (70-80°F).

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves, protective clothing and eye protection. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Do not breathe mist, vapors or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state and federal regulations.

WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Zinc (7440-66-6), Heptane (142-82-5), Propane/n-Butane (68476-86-8), Acetone (67-64-1), Xylene (1330-20-7), Ethyl benzene (100-41-4).

HEALTH	2
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	B



PACKAGING INFORMATION

12 – 16 oz. cans per case, 14 oz. net weight