

BREACH

SUPER PENETRANT



DESCRIPTION

BREACH is a penetrating lubricant that loosens fasteners or bolts that are stuck or frozen in place so they can be removed or separated. **BREACH** seeps into crevices or small spaces between threaded parts to release them. **BREACH** can displace moisture and prevent corrosion between fasteners.

APPLICATIONS

For use in machine shops, factories, assembly plants, electronics repair shops, air conditioning repair, auto body shops, locksmiths, auto mechanic shops, oil rigs.

FEATURES & BENEFITS

- Breaks up rust
- Quickly loosens frozen bolts
- Displaces moisture
- Lubricating Action

SPECIFICATIONS

<p>FORM: Solvent-Based Liquid ODOR: Hydrocarbon COLOR: Colorless DETERGENCY: None TOXICITY: 200 mg/m3 ACGIH TLV WETTING ABILITY: Saturates STORAGE STABILITY: 1 Year+ COLD STABILITY: 0°F PHOSPHATES: None</p>	<p>FLASH POINT: >200°F FLAME EXTENSION: N/A SOLUBILITY IN WATER: Insoluble. SPECIFIC GRAVITY: .84 VOC: 17% pH: N/A PROPELLANT: N/A EVAPORATION RATE: N/D BIODEGRADABILITY: No</p>
---	---

LABEL INFORMATION

BREACH SUPER PENETRANT

A penetrating lubricant that loosens fasteners or bolts that are stuck or frozen in place so they can be removed or separated. **BREACH** seeps into crevices or small spaces between threaded parts to release them. **BREACH** can displace moisture and prevent corrosion between fasteners.


USES: For use in machine shops, factories, assembly plants, electronics repair shops, air conditioning repair, auto body shops, locksmiths, auto mechanic shops, oil rigs.

DIRECTIONS: Spray or brush on liberally directly on area to be treated. Reapply periodically as required.

DANGER: May be fatal if swallowed and enters airways. If swallowed: Immediately call a poison center or a doctor. Do NOT induce vomiting. Store Locked-Up. Dispose of contents and container in accordance with local, state and federal regulations.

CONTAINS (CAS#): Distillates (petroleum), hydrotreated light (64742-47-8), Naphtha (petroleum), hydrotreated heavy (64742-48-9), Dipropylene glycol n-propyl ether (29911-27-1), Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5), Oleic acid (112-80-1).

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

Available in 5 gallon pails, and 55 gallon drums.