

UP AND AWAY

FLOATING LIFT STATION CLEANER



DESCRIPTION

UP AND AWAY quickly dissolves heavy grease and fat accumulations in a lift station. Powerful solvent formula dissolves tough build ups on the walls of the lift station and keeps future build up to a minimum. Removes most sewer odors and gases caused by vertical buildup of grease, fat, sewage and magnesium soap. For use in wet wells, grease traps, sewage treatment plants, vault toilets, and sanitary and storm sewers. Keeps hoses and pumps functioning properly.

APPLICATIONS

Effectively breaks down vertical accumulation of sewage, magnesium soap, fatty acid, grease.

FEATURES & BENEFITS

- Rapid emulsification properties
- No brush or scrub concentrate
- Removes the source of foul odors
- Industrial municipal detergent formula

SPECIFICATIONS

| | |
|------------------------------------|---------------------------------|
| FORM: Liquid | FLASH POINT: 40.5°F |
| ODOR: Mild Aromatic | BOILING POINT: N/A |
| COLOR: Clear Orange | SOLUBILITY IN WATER: 0% |
| DETERGENCY: N/A | SPECIFIC GRAVITY: 0.770 |
| TOXICITY: 100 ppm OSHA PEL | % VOLATILE BY VOLUME: 6% |
| WETTING ABILITY: Excellent | pH: N/A |
| STORAGE STABILITY: 1 Year + | VISCOSITY: Thin |
| COLD STABILITY: 32°F | EVAPORATION RATE: Slow |
| PHOSPHATES: N/A | BIODEGRADABILITY: Yes |

LABEL INFORMATION

UP AND AWAY FLOATING LIFT STATION CLEANER

UP AND AWAY Floating Lift Station Degreaser quickly dissolves heavy grease and fat accumulations in a lift station. Powerful solvent formula dissolves tough build ups on the walls of the lift station and keeps future build up to a minimum. Removes most sewer odors and gases caused by vertical buildup of grease, fat, sewage and magnesium soap. For use in wet wells, grease traps, sewage treatment plants, vault toilets, and sanitary and storm sewers. Keeps hoses and pumps functioning properly.

DIRECTIONS

Pour **UP AND AWAY** directly into the lift station. For ideal performance an 8 to 12 inch layer is required. The fluctuation of the water level during the operation of the lift station will degrease and clean the side walls of the lift station wall.

Individual lift station activity will determine the necessary frequency of application. One application can last up to 3 months.


DANGER: Flammable liquid and vapor. Causes eye irritation. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Keep container tightly closed. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire use dry chemical, foam, or carbon dioxide. Store in a well-ventilated place. Keep cool. Dispose of contents and container in accordance with local, state, and national regulations. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up.

For large quantities: Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

CONTAINS (CAS #): Aliphatic Petroleum Hydrocarbon (8052-41-3), 1,3,5-Trimethylbenzene (108-67-8), Xylene (1330-20-7).

| | |
|--------------|---|
| HEALTH | 1 |
| FLAMMABILITY | 2 |
| REACTIVITY | 0 |
| PERSONAL | B |



PACKAGING INFORMATION

Available in 4x1 gallons, 5 and 6 gallon pails and 55 gallon drums.