

VROOM

STARTING FLUID



DESCRIPTION

VROOM is designed to aid gasoline and diesel engines with quick and easy starting power in cold, wet or freezing weather. Prevents excessive battery drain. Functions after use as a corrosion inhibitor and upper cylinder lubricant. Note: Do not use this product on glow plugs.

APPLICATIONS

For use on all automobile, truck, lawn mower, and upper cylinder lubricant, boat, chain saw, tractor, and other motors. Areas of use include machine shops, auto repair shops, truck stops, marinas, lawn mower repair shops and company fleet shops.

FEATURES & BENEFITS

- Provides quick, easy start-up in all weather conditions
- For use on all internal combustion, gasoline, and diesel engines
- Reduces battery drain

SPECIFICATIONS

FORM: Solvent Based Aerosol
 ODOR: Ether
 COLOR: Clear
 DETERGENCY: N/A
 TOXICITY: 400 ppm
 WETTING ABILITY: N/A
 STORAGE STABILITY: 1 Year
 COLD STABILITY: -40°F
 PHOSPHATES: None

FLASH POINT: -10°F
 FLAME EXTENSION: N/A
 SOLUBILITY IN WATER: Immiscible
 SPECIFIC GRAVITY: N/A
 % VOLATILE BY VOLUME: 100%
 pH: N/A
 PROPELLANT: Carbon Dioxide
 EVAPORATION RATE: None
 BIODEGRADABILITY: No

LABEL INFORMATION

VROOM STARTING FLUID

VROOM aids gasoline and diesel engines in fast and easy start-up in all temperatures and weather conditions. Prolongs battery and starter life. Contains upper cylinder lubricants and anti-corrosive additives. Note: Do not use this product on glow plugs.


APPLICATIONS: For use on the following engines: automobiles, trucks, lawn mowers, boats, chainsaws, tractors, and other internal combustion engines. For use by automobile dealerships, auto repair shops, truck stops, equipment and auto rental outlets, marinas, lawn mower repair services, and company fleet divisions.

DIRECTIONS FOR USE Spray into air intake system (air cleaner, carburetor, or intake manifold) for 2 seconds prior to starting engine. Repeat if necessary. Do not flood engine. Avoid over-use.

DANGER: Extremely flammable. Harmful or fatal if swallowed or inhaled. May be harmful if absorbed through skin. Causes eye irritation. Contents under pressure. Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Avoid breathing vapor. Use only with adequate ventilation. Keep away from heat, sparks and flame. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Keep out of direct sunlight. Prolonged or repeated overexposure may cause lung, nervous system, heart, gastrointestinal, and blood effects. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. KEEP OUT OF REACH OF CHILDREN. SEE MATERIAL SAFETY DATA SHEET.

CONTAINS (CAS#): Heptane (142-85-5), Diethyl Ether (60-29-7), Carbon Dioxide (124-38-9), Propane (74-98-6), Isobutane (75-28-5).

HEALTH	2
FLAMMABILITY	4
REACTIVITY	2
PERSONAL	B



PACKAGING INFORMATION

12 – 16 oz cans per case, 10.7 oz net weight