

# FLEETMASTER

## HEAVY DUTY CAR & TRUCK WASH



### DESCRIPTION

**FLEETMASTER** is a heavy duty automobile and truck detergent. Removes road film when used through a pressure washer with 600 psi. A unique combination of emulsifiers, wetting agents and soil suspension agents. Very effective even in hard or cold water. Removes the grease, grime and soils along with road film that conventional automotive cleaners can't touch. Biodegradable.

### APPLICATIONS

An excellent product to be used on equipment, tractors, automobiles, trucks, and trailers. Can be used by auto dealers, equipment dealers, make ready shops, car washes, freight companies and auto repair shops.

### FEATURES & BENEFITS

- Economical—dilutes one to four ounces per gallon of water depending on degree of buildup
- Works in hard or soft, warm or cold water, warm or cold weather
- All components are biodegradable

### SPECIFICATIONS

**FORM:** Liquid  
**ODOR:** Bland  
**COLOR:** Green  
**DETERGENCY:** Strong  
**TOXICITY:** Non-hazardous  
**WETTING ABILITY:** Excellent  
**STORAGE STABILITY:** 1 Year  
**COLD STABILITY:** 32°F  
**PHOSPHATES:** 9%

**FLASH POINT:** N/A  
**BOILING POINT:** N/A  
**SOLUBILITY IN WATER:** 100%  
**SPECIFIC GRAVITY:** 1.12  
**% VOLATILE BY VOLUME:** 95%  
**pH:** 12.8  
**VISCOSITY:** Medium  
**EVAPORATION RATE:** Slow  
**BIODEGRADABILITY:** Yes

### LABEL INFORMATION

#### FLEETMASTER HEAVY DUTY CAR & TRUCK WASH

This synergistically formulated liquid removes road film and other soils that have bonded to the surfaces of cars and trucks. A powerful all purpose car and truck wash that leaves surfaces clean and shiny. Rinses free with no residual film. Designed to be used on automobiles, trucks, buses, aircraft, heavy equipment. Biodegradable.


**DIRECTIONS FOR USE:** With pressure washer (pressure-600 psi or greater): Set metering system so that one ounce of product per gallon of water is applied to vehicle surface. Hold wand so that the sprayhead is at the distance from surface recommended by equipment manufacturer. For extra road film buildups, increase solution strength until effective removal of soil is accomplished. For COLD WATER follow same directions as above, except solution strength will have to be increased to 4 ounces of product per gallon of water.

**WARNING:** Causes skin and serious eye irritation.

Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**CONTAINS (CAS #):** Water (7732-18-5), Tetrapotassium Pyrophosphate (7320-34-5), Nonionic Surfactant (127087-87-0), Coco fatty acids (132647-09-7), Sodium Silicate (1344-09-8).

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL	B



### PACKAGING INFORMATION

Available in 4x1 gallons, 5 and 6 gallon pails, and 55 gallon drums.