

# KOPPER LUBE

## COPPER-BASED ANTI-SEIZE

### DESCRIPTION

**KOPPER LUBE** is a copper-based anti-seize lubricant formulated to withstand high temperatures and extreme pressures. Continues ground conductivity better than ordinary lubricants. Seals out moisture, gases and corrosive fluids from threaded connections. Copper-Moly combination prevents seizing, galling and premature wear. Contains rust and corrosion inhibitors.

### APPLICATIONS

Designed for use on threaded connections, piping, suds, lamp sockets, pump housings, flanges, studs, exhaust manifold bolts, compressor heads, autoclaves, lathe centers and more. Areas of use include automotive, industrial, marine and construction industries.

### FEATURES & BENEFITS

- Hammer & Chisel Paste
- Protects Against Rust, Corrosion and Oxidation
- Copper-Moly Combo Prevents Seizing
- Temperature Range of 0° to 350°F
- Improves Conductivity

### SPECIFICATIONS

**FORM:** Thick paste

**ODOR:** Bland

**COLOR:** Copper

**DETERGENCY:** N/A

**TOXICITY:** Non-hazardous

**WETTING ABILITY:** N/A

**STORAGE STABILITY:** 1 Year +

**COLD STABILITY:** 0°F

**PHOSPHATES:** None

**FLASH POINT:** >425°F

**BOILING POINT:** Decomposes

**SOLUBILITY IN WATER:** 0%

**SPECIFIC GRAVITY:** 0.87

**% VOLATILE BY VOLUME:** 0%

**pH:** N/A

**VISCOSITY:** Very Thick

**EVAPORATION RATE:** Slow

**BIODEGRADABILITY:** No

### LABEL INFORMATION

#### KOPPER LUBE COPPER-BASED ANTI-SEIZE

KOPPER LUBE is a copper-based anti-seize lubricant formulated to withstand high temperatures and extreme pressures yet continues ground conductivity better than ordinary lubricants. Seals out moisture, gases and corrosive fluids from threaded connections. Copper-Moly combination prevents seizing, galling and premature wear. Contains rust and corrosion inhibitors to assure long life of connectors. Designed for use on threaded connections, all piping, lamp sockets, bus bars, compression connectors, battery lugs and cables, fuse clips, grounding clamps, bolted connectors, fittings and connections, taps, lugs, hydraulic hammers and more.


**DIRECTIONS:** Clean surface to be treated. Apply with brush to insure contact over irregular areas.

**CAUTION:** Keep out of reach of children. Avoid contact with eyes and clothing.

**WARNING:** Cancer and birth defects or other reproductive harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**CONTAINS (CAS#):** Polybutene (9003-29-6), Copper (7440-50-8), Fumed silica (amorphous) (112945-52-5), Polysulfides, di-tert-dodecyl (689425-15-0), Acetone (67-64-1).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



### PACKAGING INFORMATION

Available in 8 oz. brush top cans (12/case), 35 lb. pails and 120 and 400 lb. drums.