

QuestSpecialty

Big Red

Super Impact Non-Melt
E.P. Grease

Big Red

Super Impact Non-Melt
E.P. Grease

Grasa E.P. con Súper
Impacto Sin-Derretirse

Bentone Based Formula
High Shock & Impact Resistance
Temperature Range of 0° to 300°F

All Weather Performance
Extreme Pressure Additives
For High Loads

Unique Rust & Corrosion Inhibitors
Resists: Acids, Water, Salt Spray,
Dust & Dirt

CAUTION/PRECAUCIÓN:
KEEP OUT OF REACH OF CHILDREN
SEE ADDITIONAL CAUTIONS ON BACK PANEL

NO SE DEJE AL ALCANCE DE LOS NIÑOS
VEA PRECAUCIONES ADICIONALES EN EL PÁNTEL TRASERO

NET CONTENTS: 14 OZ. (397 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834 • 713.896.8188

A multi-use grease for hundreds of automotive, marine and agricultural applications. Extreme pressure additives give resistance to shock impact. Bentone based formula does not liquefy at high temperatures like soap based greases, yet remains pumpable at low temperatures. Forms a protective film, resists rust and corrosion. Resists chemical break down and oxidation. This waterproof lubricant will not wash out even by boiling water and steam.

film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

PRECAUCIÓN: No se deje al alcance de los niños. Puede causar irritación a los ojos. El contacto prolongado puede causar irritación de la piel. Si es ingerido, puede causar náusea, vómito y diarrea. Si hay contacto con los ojos, enjuague con agua, vea a un médico si la sensación aceitosa persiste. Si hay contacto con la piel, lave con agua y jabón. Para la ingestión de más de 8 onzas contacte al médico.

DIRECTIONS FOR USE: Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

CONTAINS (CAS#): Naphthenic Oil (64742-52-5), Nykon 77 (68953-58-2), Baragel 3000 (N/A), Paratac (0090003-27-4), Heavetex (9003-31-0).

Pump in new grease.

NLGI GRADE: 3

MODO DE EMPLEO: Inyecte grasa nueva hasta que la grasa vieja salga. Remueva la grasa vieja si es posible.

Para conexiones de tipo bola, llene hasta que la grasa vieja salga. Limpie las áreas expuestas con desengrasante para remover la grasa vieja. Inyecte nueva grasa.

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily

Made in USA 600005050



ITEM L1030001-145G