SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Surround

PRODUCT CODE: 5880

RECOMMENDED USE: Cold Pipe Insulation Spray

RESTRICTIONS ON USE: This product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal. After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/product is and can only be distributed in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion-sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing; (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal; and (14) Export.

COMPANY NAME: QuestSpecialty Corporation

COMPANY ADDRESS: P.O. Box 624, Brenham, TX 77834

COMPANY PHONE: 800-231-0454 **EMERGENCY PHONE:** 800-255-3924

SECTION II - HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 2

Gases Under Pressure: Liquefied Gas

Skin Irritant: Category 2 Eye Irritant: Category 2A Carcinogenicity: Category 2

Specific Target Organ Toxicity (Single Exposure): Category 3 Specific Target Organ Toxicity (Repeated Exposure): Category 2

HAZARD STATEMENT(S): WARNING: Flammable aerosol. Contains gas under pressure; may explode if heated. May cause respiratory irritation, drowsiness or dizziness. Causes skin and serious eye irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wear protective gloves and eye protection. Wash hands thoroughly after handling. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing dust, fumes or mist. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a posion center or doctor if you feel unwell. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:









HAZARDS NOT OTHERWISE CLASSIFIED: N/A

Safety Data Sheet Surround

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTCAS NUMBERPERCENTMethylene Chloride75-09-230-60%Propane/n-Butane68476-86-815-40%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION IV - FIRST AID MEASURES

EYES: Remove contact lenses. Flush with water for at least 15 minutes. See a physician if irritation persists.

INGESTION: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention if irritation persists.

INHALATION: If inhaled: Remove person to fresh air and keep comfortable for breathing.

SKIN: Wash thoroughly with soap and water. Seek medical attention if irritation develops.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision. Skin: defatting and dermatitis. Inhalation: Irritation. Oral: abdominal irritation, nausea, vomiting, and diarrhea

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, lungs, blood, or central nervous system.

NOTE TO PHYSICIAN: Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This product contains ingredients that may be anticipated to be a carcinogen.

SECTION V - FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Carbon dioxide, foam, and water fog.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLAMMABLE. Contents under pressure. Exposure to temperatures above 120 °F may cause bursting.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, hydrogen chloride, phosgene.

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Remove sources of ignition such as pilot lights. Material is heavier than air and can settle in low lying areas in Flammable concentrations, ventilate area. Product will undergo rapid evaporation. Use absorbent or spill sweep to clean.

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations. Do not flame cut, braze or weld. Empty container very hazardous!

RCRA STATUS: Waste solvent likely considered F001, hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII - HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: May attack certain plastics, rubber and coatings. Incompatible with strong oxidizers and caustics and chemically active metals such as aluminum, magnesium powder, sodium, potassium and lithium.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Methylene Chloride	25 ppm	50 ppm
Propane/n-Butane	1000 ppm	1000 ppm

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses/goggles and chemical resistant gloves.

Safety Data Sheet

Surround

ADDITIONAL MEASURES: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear Liquid. **ODOR:** Chlorinated solvent.

ODOR THRESHOLD: 21 mg/m³ (methylene chloride).

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: > 140°F

FLASH POINT: N/D EVAPORATION RATE: >2

FLAMMABILITY (solid/gas): Flammable aerosol.

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D UPPER FLAMMABILITY LIMIT: N/D EXPLOSIVE LIMIT LOWER (%): N/D EXPLOSIVE LIMIT UPPER (%): N/D VAPOR PRESSURE (mm Hg): >100 VAPOR DENSITY (AIR=1): > 2

RELATIVE DENSITY (H2O=1): 1.2 @ 77°F (25°C)

SOLUBILITY(IES): 0% in water.

PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D

AUTOIGNITION TEMPERATURE: N/D **DECOMPOSITION TEMPERATURE:** N/D

VISCOSITY: N/D

SECTION X - STABILITY AND REACTIVITY

REACTIVITY: None known.

CHEMICAL STABILITY: Stable under recommended storage conditions.

POSSIBLE HAZARDOUS REACTIONS: None known.

CONDITIONS TO AVOID: Excessive heat. Sources of ignition.

INCOMPATIBLE MATERIALS: May attack certain plastics, rubber and coatings. Incompatible with strong oxidizers and caustics

and chemically active metals such as aluminum, magnesium powder, sodium, potassium and lithium.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, hydrogen chloride gas and phosgene gas.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Methylene chloride (75-09-2): LD₅₀ (Oral, Rat) > 2000 mg/kg; LD₅₀ (Dermal, Rat) > 2000

mg/kg; LC₅₀ (Inhalation, Rat) 52000 mg/m³. **ROUTES OF ENTRY:** Eyes, Ingestion, Inhalation, Skin

EYES: Causes irritation, redness, temporary eye damage.

INGESTION: Nausea, vomiting, headaches, abdominal pain, diarrhea, dizziness, pulmonary edema, unconsciousness or death.

INHALATION: May cause respiratory tract irritation, headaches, nausea, vomiting and may cause fatigue. Excessive or prolonged exposure may cause dizziness and unconsciousness.

SKIN: Causes mild irritation, dryness, localized defatting.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-exsiting skin disorders, respiratory, liver, kidney,

cardiovascular or pulmonary illnesses.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Irritation

Oral: abdominal irritation, nausea, vomiting, and diarrhea

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to skin, kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, lungs, blood, or central nervous system.

CARCINOGENICITY: OSHA: Yes ACGIH: A3 - Animal Carcinogen NTP: Suspected IARC: 2B - Possible OTHER: CA Prop 65

control of the contro

Safety Data Sheet Surround

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: Not established.

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATIVE POTENTIAL: This product is not expected to bioaccumulate.

MOBILITY IN SOIL: This product is mobile in soil. **OTHER ADVERSE EFFECTS:** None known.

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations. Do not flame cut, braze or weld. Empty container very hazardous!

RCRA STATUS: Waste solvent likely considered F001, hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1 (6.1) UN/NA NUMBER: UN1950 PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable, containing substances in Division 6.1, Packing Group III.

HAZARD CLASS/DIVISION: 2.1 (6.1) UN/NA NUMBER: UN 1950 PACKING GROUP: N/A

SHIPPING BY WATER: VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, toxic. HAZARD CLASS/DIVISION: 2.1 (6.1) UN/NA NUMBER: UN 1950 PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Methylene chloride (75-09-2) Reportable Quantity = 1,000 pounds.

SARA 311/312 HAZARD CATEGORIES: Acute Health, Chronic Health

SARA 313 REPORTABLE INGREDIENTS: Methylene chloride (75-09-2).

STATE REGULATIONS: California Proposition 65: WARNING: This product can expose you to chemicals including Dichloromethane (Methylene Chloride), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov. Methylene chloride (75-09-2): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CT, FL, IL, LA, MA, MI, MN, NJ, NY, PA, RI, TN.

INTERNATIONAL REGULATIONS: All components are listed or exempted.

VOLATILE ORGANIC COMPOUNDS (VOC): 32%

This product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal. After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/product is and can only be distributed in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion-sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing; (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and

Safety Data Sheet

Surround

architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal; and (14) Export.

NFPA HEALTH: 2
NFPA FLAMMABILITY: 2
NFPA REACTIVITY: 0
NFPA OTHER: None
HMIS PROTECTION: B

7.35# Methylene Chloride per case

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Craig Bernard DATE PREPARED: 07/26/2013 REVISION DATE: 11/26/2024

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.