SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Clean Brake

PRODUCT CODE: 8110

RECOMMENDED USE: Brake Cleaner **RESTRICTIONS ON USE:** None Known

COMPANY NAME: QuestSpecialty Corporation

COMPANY ADDRESS: P.O. Box 624, Brenham, TX 77834

COMPANY PHONE: 800-231-0454 **EMERGENCY PHONE:** 800-255-3924

SECTION II - HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1

Dissolved Gas

Skin Irritant: Category 2 Eye Irritant: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category 3

Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause respiratory irritation, drowsiness or dizziness. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapor and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state and federal regulations.

SYMBOL:









HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Acetone	67-64-1	30-60%
Heptane	142-82-5	30-60%
Carbon Dioxide	124-38-9	7-13%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: Do not induce vomitting. Seek medical attention.

INHALATION: Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

Safety Data Sheet

Clean Brake

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Irritation

Oral: abdominal irritation, nausea, vomiting, and diarrhea **CHRONIC HEALTH HAZARDS:** None Known

NOTE TO PHYSICIAN: There is no specific treatment regimen. Treatment of overexposure should be directed at the control of

symptoms and the clinical condition of the patient.

SECTION V - FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry Chemical, Alcohol Foam, CO₂ **UNSUITABLE EXTINGUISHING MEDIA:** Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Remove any source of ignition. Use non-sparking tools and equipment. Use absorbent on spill sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.

WASTE DISPOSAL: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste solvent likely considered F003, Flammable, Non-halogentated solvent, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII - HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use.

OTHER PRECAUTIONS: Keep out of the reach of children. Follow label directions exactly. Vapors may collect in low lying areas.

INCOMPATIBILITY: Concentrated nitric and sulfuric acid, oxidizers, chloroform, alkalis, chlorinated compounds, acids.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	500 ppm
Heptane	400 ppm	400 ppm
Carbon Dioxide	5000 ppm	5000 ppm

ENGINEERING CONTROLS / VENTILATION: Ambient ventilation suitable, forced ventilation should not be required **RESPIRATORY PROTECTION:** Not required with normal use. Wear NIOSH/MSHA approved respiratory protection if exposure

limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

ADDITIONAL MEASURES: Wash hands and all equipment throughly after use.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, Colorless Spray

ODOR: Aliphatic solvent odor **ODOR THRESHOLD:** N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: ND

FLASH POINT: N/D

EVAPORATION RATE: > 1

FLAMMABILITY(solid/gas): Extremely Flammable Aerosol **UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:**

LOWER FLAMMABILITY LIMIT: N/D

Safety Data Sheet

Clean Brake

UPPER FLAMMABILITY LIMIT: N/D EXPLOSIVE LIMIT LOWER (%): N/D EXPLOISVE LIMIT UPPER (%): N/D VAPOR PRESSURE (mm Hg): N/D VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H2O=1): 0.74-0.78 @ 77°F (25°C)

SOLUBILITY(IES): 0%

PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D

AUTOIGNITION TEMPERATURE: N/D **DECOMPOSITION TEMPERATURE:** N/D

VISCOSITY: N/D

SECTION X - STABILITY AND REACTIVITY

REACTIVITY: If exposed to strong oxidizers, presents explosion hazard.

CHEMICAL STABILITY: Stable

POSSIBLE HAZARDOUS REACTIONS: None Known

CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.

INCOMPATIBLE MATERIALS: Concentrated nitric and sulfuric acid, oxidizers, chloroform, alkalis, chlorinated compounds, acids

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon

SECTION XI - TOXICOLOGICAL INFORMATION

 $\textbf{TOXICOLOGICAL INFORMATION: Acetone} \ (67\text{-}64\text{-}1) \ \text{LD}_{50} \ (\text{Oral, Rabbit}) \ 5340 \ \text{mg/kg; LD}_{50} \ (\text{Dermal, Rabbit}) \ 20000 \ \text{mg/kg} \ \textbf{n-Heptane} \ (142\text{-}82\text{-}5) \ \text{LD}_{50} \ (\text{Oral, Rat}) \ > 15000 \ \text{mg/kg; LD}_{50} \ (\text{Dermal, Rabbit}) \ > \ 3160 \ \text{mg/kg; LC}_{50} \ (\text{Inhalation, Rat}) \ 103 \ \text{mg/l/4h}$

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes irritation, defatting.

INGESTION: Causes gastrointestinal irritation, nausea, diarrhea, absorption through gastrointestinal tract may produce symptoms of central nervous system depression ranging from light headedness to unconsciousness.

INHALATION: Dizziness, headache, nausea, depression of central nervous system, prolonged exposure may lead to unconsciousness **SKIN:** Brief contact is not irritating. May cause irritation, localized defatting, redness, itching with prolonged or repeated contact. Can be absorbed through the skin with prolonged and widespread contact.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-exsiting skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Irritation

Oral: abdominal irritation, nausea, vomiting, and diarrhea CHRONIC HEALTH HAZARDS: None Known

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: Acetone (67-64-1) LC₅₀ (Trout, 96hr) 5540 mg/L; LC₅₀ (Bluegill, 96hr) 8300 mg/L; LC₅₀ (Fathead Minnow, 96hr)

7500 mg/L **n-Heptane** (142-82-5) EC₅₀ (Daphnia 1) 0.2 mg/l (LC₅₀; Other; 96h; Chaetogammarus marinus)

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATIVE POTENTIAL: Components in this mixture can bioaccumulate in aquatic organisms.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: This material is toxic to aquatic life.

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste solvent likely considered F003, Flammable, Non-halogentated solvent, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1 UN/NA NUMBER: UN 1950

Safety Data Sheet

Clean Brake

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable

HAZARD CLASS/DIVISION: 2.1 **UN/NA NUMBER:** UN 1950

PACKING GROUP: N/A

SHIPPING BY WATER: VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols HAZARD CLASS/DIVISION: 2.1 UN/NA NUMBER: UN 1950 PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Acetone (67-64-1) Reportable Quantity = 5.000 lbs

SARA 311/312 HAZARD CATEGORIES: Acute Health, Fire, Pressure.

SARA 313 REPORTABLE INGREDIENTS: None

STATE REGULATIONS: Acetone (67-64-1) Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, Illinois chemical safety act, New York release reporting list, RTK - RI, PA, FL, MN, MA, NJ; Massachusetts spill list, New Jersey spill list, Louisiana spill reporting, California List of Hazardous Substances (8 CCR 339): Acetone TSCA 8(b) inventory: Acetone TSCA 4(a) final test rules: Acetone TSCA 8(a) IUR: Acetone Heptane (142-82-5) California Director's List of Hazardous Substances, Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, New Jersey RTK, Massachusetts RTK, Minnesota RTK, Pennsylvania RTK, Rhode Island RTK

INTERNATIONAL REGULATIONS: Acetone (67-64-1) Australia, Japan, Korea, United Kingdom, Canada, WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC). p. 6; DSCL (EEC): R11- Highly flammable. R36- Irritating to eyes. S9- Keep container in a well-ventilated place. S16-Keep away from ignition sources. S26- In case of eye contact, rinse immediately with plenty of water and seek medical advice. Heptane (142-82-5): Australia, Canada, China, Europe, Japan, South Korea, New Xealand, Philippines, Switzerland, Taiwan.

VOLATILE ORGANIC COMPOUNDS (VOC): 44.6%

NFPA HEALTH: 1
NFPA FLAMMABILITY: 3
NFPA REACTIVITY: 0
NFPA OTHER: None
HMIS PROTECTION: B

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Craig Bernard DATE PREPARED: 02/23/2021 REVISION DATE: 11/13/2024

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.