QuestSpecialty

Product # 3230

Technical Data Report

Top Hat water based total release odor control



DESCRIPTION

TOP HAT neutralizes all types of malodors, leaving a pleasant mulberry fragrance. Effectively eliminates odors caused by urine, feces, decay, rancidity, animals, fire, tobacco smoke, cooking and mildew. Each can neutralizes odors in up to 6,000 cu. ft. of space. This product is not a cover up but chemically destroys the odor molecule, thus eliminating offensive odors.

APPLICATIONS

Freshens stale air and fabrics without the worry of wetness, staining and residue. Deodorizes the area leaving it smelling fresh and clean. Areas of use include homes, meeting rooms, offices, hospitals, nursing homes, auto detail shops, veterinary clinics, sports clubs, shopping malls, bathrooms, and eating establishments.

FEATURES & BENEFITS

- · Non-staining, dry spray leaves no wet fallout on floors or furniture
- Pleasant mulberry fragrance neutralizes hundreds of malodors

SPECIFICATIONS

FORM: Water Based Aerosol ODOR: Mulberry COLOR: White TOXICITY: 400ppm OSHA PEL STORAGE STABILITY: 1 year + COLD STABILITY: <32°F PHOSPHATES: None FLASH POINT: <100°F FLAME EXTENSION: >18" SPECIFIC GRAVITY: 0.790 VOC: 25% pH: 7 PROPELLANT: Hydrocarbon EVAPORATION RATE: Slow BIODEGRADABILITY: No

· Meets all current VOC standards

LABEL INFORMATION

TOP HAT

TOTAL RELEASE ODOR CONTROL

This unique product neutralizes all types of malodors. It is effective in eliminating odors caused from urine, feces, decay, rancidity, animals, fire, tobacco smoke, cooking and mildew. Each can neutralizes and destroys odors in up to 6,000 cubic feet of space.

DIRECTIONS FOR USE: DO NOT use more than one fogger per room. DO NOT use in small, enclosed spaces such as closets, cabinets, or under counters or tables. DO NOT use in a room 5 feet by 5 feet or smaller; instead, allow fog to enter from other rooms. Turn off ALL ignition sources such as pilot lights (shut off gas valves), other open flames, or running electrical appliances that cycle off and on (i.e., refrigerators, thermostats, etc.). Call your gas utility or management company if you need assistance with your pilot lights. Do not use this unit in an area less than 100 cubic feet. Close all windows and turn off air conditioning or heating unit. Place can on raised surface near middle of room. Spread paper or cloth directly below can for protection. To lock valve into open position for total discharge, press valve button all the way down, locking the catch. Then place fogger down and immediately leave the room. Do not disturb area for at least 2 hours. Ventilate room for 30 minutes before re-entering.

WARNING: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause an allergic skin reaction. Keep away from heat, sparks, open flames or hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Avoid breathing mist, vapors or spray. Contaminated work clothing must not be allowed out of the workplace. Wash contaminated clothing before reuse. Dispose of contents and container in accordance with local, state and federal regulations.

CONTAINS (CAS#): Water (4432-18-5), Propane (74-98-6), Hydrotreated light alkanes (64742-47-8), Acetone (67-64-1), Sorbitan oleate (1338-43-8), Diethyl phthalate, d-Limonene, Linalool. For more ingredient information visit www.questspecialty.com.

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION