

QUIKLEEN II

SOLVENT CLEANER



DESCRIPTION

QUIKLEEN II is a USDA authorized non-flammable and non-conductive parts cleaner. Safe for use on metal parts, electric motors and electronic subassemblies. Quickly cleans oil, grease and dirt from parts without leaving residue. Displaces moisture from electric motors. Can be used while equipment is operating. Dielectric strength of 29,000 volts. Contains no 1,1,1 Trichloroethane. Product must be tested prior to using on any plastic. Due to VOC regulations, not available for sale in CA, CT, MD, NJ, MA, ME, MI, NY, DE, DC, IL, RI, UT.

APPLICATIONS

For electrical motors, ignition systems, electronic parts, and refrigeration equipment. Areas of use include machine shops, factories, industrial plants, offices, automotive and bus repair shops, printing industry, electrical maintenance services, marine sales and repair.

FEATURES & BENEFITS

- Fast drying
- Contains no oil, leaves no residue
- Non-flammable and non-conductive
- Non-ozone depleting

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 25 ppm OSHA PEL
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: None
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.52
% VOC: 50%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Fast
BIODEGRADABILITY: None

LABEL INFORMATION

QUIKLEEN II SOLVENT CLEANER

A highly concentrated solvent designed to remove dirt, grease, oil and grime from metallic and nonmetallic surfaces. Cleaning is quick and simple without the danger of injury to working parts. Ideally suited for use on electric motors even while running, electronic equipment, ignition systems, generators, power tools, and for air conditioning, refrigeration and all types of mechanical equipment.

NOTE: Do not use on automatic electronic process control or monitoring systems, computers or data processing equipment. May affect certain plastics. Test before using.

Authorized by USDA for use in federally inspected meat and poultry plants.

DIRECTIONS: Remove cap and spray generously over the surface to be cleaned until completely wet. Allow the solvent to set for a minute, then wipe or rinse off with a second spray. On heavily encrusted areas use a brush. Product is nonflammable and nonconductive so it can be used while motors and equipment are operating.

DANGER: Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May cause cancer. Suspected of causing genetic defects. May cause an allergic skin reaction.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves, eye protection and protective clothing. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. Contaminated work clothing must not be allowed out of the workplace. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Dispose of contents and container in accordance with local, state, and national regulations.

WARNING: This product can expose you to chemicals including Trichloroethylene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Trichloroethylene (79-01-6), Tetrachloroethylene (127-18-4), Carbon Dioxide (124-38-9).

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	C



PACKAGING INFORMATION

5120: 12 – 16 oz. cans per case, 16 oz. net weight

5130: 12 – 20 oz. cans per case, 18 oz. net weight (Private Label Only)