



# Technical Data Report

## FUSION AP MISTING SPRAY ADHESIVE



### DESCRIPTION

**FUSION AP** is a misting pressure sensitive spray adhesive designed to be used on a wide range of surfaces. Creates both permanent and temporary bonds on many surfaces. Excellent for porous or uneven surfaces as well as smooth surfaces. Waterproof, flexible, transparent, non-staining adhesive sets quickly.

### APPLICATIONS

Effectively bonds such surfaces as labels, cartons, cloth, plastic, ceramic, glass, wood, Formica®, leather, foam, polyethylene sheeting, etc. Cleans up with mineral spirits. Areas of use include printers, industrial plants, shipping departments, schools, construction areas, auto upholstery repair shops and furniture manufacturers.

### FEATURES & BENEFITS

- All purpose misting spray
- Quick adhesion & tacking
- Permanent or temporary bonds
- BONDS: Labels, cartons, cloth, plastic, polyethylene sheeting, foam, ceramic, glass, wood, Formica® and more

### SPECIFICATIONS

<b>FORM:</b> Solvent-Based Aerosol	<b>FLAME EXTENSION:</b> 18"+
<b>ODOR:</b> Solvent	<b>SOLUBILITY IN WATER:</b> Immiscible
<b>COLOR:</b> Opaque Beige	<b>SPECIFIC GRAVITY:</b> 0.72-0.76
<b>DETERGENCY:</b> None	<b>% VOC:</b> 52.6%
<b>TOXICITY:</b> 300 ppm	<b>pH:</b> N/A
<b>WETTING ABILITY:</b> None	<b>PROPELLANT:</b> Hydrocarbon
<b>COLD STABILITY:</b> 0°F	<b>EVAPORATION RATE:</b> Medium
<b>FLASH POINT:</b> <37.8°C	<b>BIODEGRADABILITY:</b> No

### LABEL INFORMATION

#### FUSION AP MISTING SPRAY ADHESIVE

This misting pressure sensitive spray adhesive is designed to create both permanent and temporary bonds on a wide range of surfaces. Excellent for porous or uneven surfaces as well as smooth surfaces. Waterproof, flexible, transparent, non-staining adhesive sets quickly. Effectively bonds such surfaces as labels, cartons, cloth, plastic, ceramic, glass, wood, Formica®, leather, foam, polyethylene sheeting, etc. Cleans up with mineral spirits.

**DIRECTIONS FOR USE:** Shake well before using. Remove cap. Point opening in desired direction. Hold container 8–12 inches from surface to be sprayed. Press button to spray. For best results, apply adhesive using side to side spraying motion. For Temporary Bonds: Apply to surface, allow to tack and apply material to be bonded. For Permanent Bonds: Apply to both surfaces to be joined. Allow to tack and then press surfaces together. After use, invert can and spray until tip is clear to prevent clogging. If adhesive accumulates around opening in spray nozzle, wipe clear while wet. If opening becomes clogged, remove with degreasing solvent.


**DANGER:** Extremely flammable aerosol. Pressurized container: may burst if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs. May be harmful if swallowed and enters airways. Suspected of damaging fertility or the unborn child. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn even after use. Protect from sunlight. Do not expose to temperature exceeding 50°C/122°F. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash hands thoroughly after handling. Wear protective gloves, protective clothing, and eye protection. Do not breathe vapors or spray. Do not eat, drink or smoke when using this product. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF ON SKIN:** wash with plenty of water. If skin irritation occurs: Get medical help. Take off contaminated clothing and wash it before reuse. **IF SWALLOWED:** Get emergency medical help immediately. Do NOT induce vomiting. Use only outdoors or in a well-ventilated area. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if you feel unwell. Store in a wellventilated place. **IF EXPOSED OR CONCERNED:** Get medical advice/attention. Dispose of contents and containers in accordance with local, state, and national regulations.

**CONTAINS (CAS#):** Acetone (67-64-1), Hexane (110-54-3), Methyl Acetate (79-20-9), Propane/n-Butane (68476-86-8).

**VOC Category:** Mist Spray Adhesive

**VOC Limit:** Meets the VOC Standard of 65% by weight.

HEALTH	*3
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	C



### PACKAGING INFORMATION

12 – 20 oz. cans per case, 13.25 oz. net weight