

MOLI DRI

METHYLENE CHLORIDE FREE DRY FILM LUBRICANT



DESCRIPTION

MOLI DRI is a methylene chloride free dry film lubricant offering superior, long-lasting performance. Molybdenum graphite anti-seize dry coating resists dust and abrasive particles. Withstands water, oil, alkalies and most acids. Forms a strong bond to metal—will not wipe off easily. May be used at higher temperatures—will not carbonize. Formula is more readily accepted by safety directors. May be used as a release agent.

APPLICATIONS

Excellent for use in foundries, machine shops, industrial plants, automotive manufacturers, steel mills, chemical plants, shipyards, oil fields, marine and mining operations and more. Apply to oil and ore drills, pipe threads, lathe bed and rails, engines, chains and sprockets, pump assemblies, road equipment, turbines and more.

FEATURES & BENEFITS

- Reduces Friction - Retards Wear
- Non-Chlorinated
- Molybdenum Disulfide & Graphite
- Resists Pressures Up To 250,000 psi

SPECIFICATIONS

<p>FORM: Liquid ODOR: Solvent COLOR: Black DETERGENCY: N/A TOXICITY: See SDS WETTING ABILITY: None STORAGE STABILITY: 1 Year + COLD STABILITY: 0°F PHOSPHATES: N/A</p>	<p>FLASH POINT: <73.4°F BOILING POINT: N/D SOLUBILITY IN WATER: Negligible SPECIFIC GRAVITY: N/A % VOLATILE BY VOLUME: 26.6% pH: N/A VISCOSITY: N/D EVAPORATION RATE: N/D BIODEGRADABILITY: No</p>
---	--

LABEL INFORMATION

MOLI DRI METHYLENE CHLORIDE FREE DRY FILM LUBRICANT

- Withstands water, oils, alkalies and most acids
- Will not wipe off easily—chemically attracted to metal
- Permits immediate use of chain or gear after application
- Can be used at higher temperatures and will not carbonize
- Will not run off part to which applied, requires less frequent lubrication
- Resists dust and abrasive particles
- Replaces graphite
- Cleaner application

RECOMMENDED FOR: Foundries; machine shops; automotive plants; vehicle maintenance; sewing trades; paper and corrugated converting; chemical plants; marine, oil fields, and mining operations; etc.

FOR USE ON: Oil drilling equipment, pipe threads, lathe bed and rails, chains and sprockets, road equipment, oil drilling equipment, door locks and hinges, etc. Also may be used as a release agent.


DIRECTIONS: Shake or mix container well before using. Clean surface thoroughly. Apply a thin, even film by spraying or brushing. Thick coats decrease efficiency. Dries in 1 to 3 minutes. Allow to cure 30 minutes before exposing to water.

DANGER: Highly flammable liquid and vapor. Causes skin and serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to central nervous system (CNS), liver, kidneys and respiratory system through prolonged or repeated exposure. Keep away from heat, hot surface, sparks, open flames and other ignition sources. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye protection. IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water or shower. In case of fire use dry chemical, carbon dioxide or foam to extinguish. Store in a well-ventilated place. Keep cool. Obtain, read and follow all safety instructions before use. Wash hands thoroughly after handling. Wear protective gloves and eye protection. Do not eat, drink or smoke when using this product. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If exposed or concerned: Get medical advice or attention immediately. Do not breathe mist, vapor and spray. Use only outdoors or in a well-ventilated area. Dispose of contents and container in accordance with local, state and federal regulations.

WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Contains (CAS#): Acetone (67-64-12), Isopropyl Alcohol (67-63-0), Toluene (108-88-3), Molybdenum Disulfide (1317-33-5), Dipropylene Glycol Methyl Ether *(34590-94-8).

HEALTH	*2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

Available in 5 gallon pails and 55 gallon drums.