

# INFERNO

## MUNICIPAL SEWER COMPOUND



### DESCRIPTION

INFERNO sewer compound is a powerful chemical compound made for MUNICIPALITIES. When activated by water this product will generate heat, generate agitation, emulsify grease, emulsify oil, attack roots and digest paper. This highly effective compound provides deep penetration, is noncorroding, will attack hardened detergents and contains a highly visible tracing color.

### APPLICATIONS

Excellent for use in drain pipes and sewage lines. For use in schools, institutions, restaurants, factories, hotels/motels and municipalities.

### FEATURES & BENEFITS

- Contains highly visible tracer
- Attacks roots, oil, paper and grease
- Powerful compound

### SPECIFICATIONS

FORM: Dry Powder with Metal Chips  
 ODOR: None  
 COLOR: Off White  
 DETERGENCY: Strong  
 TOXICITY: 2 mg/m<sup>3</sup> OSHA TLV  
 WETTING ABILITY: Excellent  
 STORAGE STABILITY: 1 Year +  
 COLD STABILITY: 0°F  
 PHOSPHATES: None

FLASH POINT: N/A  
 BOILING POINT: N/A  
 SOLUBILITY IN WATER: 100%  
 SPECIFIC GRAVITY: 1.09  
 % VOLATILE BY VOLUME: 0%  
 pH: N/A  
 VISCOSITY: N/A  
 EVAPORATION RATE: <1  
 BIODEGRADABILITY: Yes

### LABEL INFORMATION

#### INFERNO MUNICIPAL SEWER COMPOUND

This product is a powerful chemical compound made for MUNICIPALITIES. When activated by water this product will generate heat, generate agitation, emulsify grease, emulsify oil, attack roots and digest paper. This highly effective compound provides deep penetration, is non-corroding, will attack hardened detergents and contains a highly visible tracing color.

**DIRECTIONS FOR USE:** In using this compound, shovel 20 to 25 lbs into strategic manholes and let this heavy duty, red colored chemical do the rest.

**FOR MUNICIPALITIES:** The recommended application is about 25 lbs shoveled or poured into strategic manholes. If larger doses are necessary, 50 lb additives of this compound may be used. This product needs water to do its work. If sewer system is dry, water should be poured down the manhole AFTER the compound is added.


**FOR INDUSTRY:** This compound is recommended for unstopping drains in food plants (particularly in packing houses where accumulations of organic matter tend to clog drainage systems) by shoveling or pouring a reasonable amount into the drainage system. This product becomes activated by water, creating considerable heat and agitation, thus removing or loosening debris and settlement in sewers and drains. It contains chemicals and metallic chips which will emulsify grease and oils and will digest paper and other materials containing a high percentage of cellulose. When added to strategic manholes, you will be able to see the effectiveness of this product throughout the sewer pipe system at later intervals by observing traces of the color in other areas of the system.

**DANGER:** Causes severe skin burns and eye damage.

Do not breathe mists. Wash hands/gloves thoroughly after handling. Wear protective gloves, eye protection, protective clothing. If swallowed: Rinse mouth, do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison control center. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents and container in accordance with local and national guidelines.

**CONTAINS (CAS#):** Sodium Hydroxide (1310-73-2), Sodium Carbonate (497-19-8), Aluminum Granules (7429-90-5).

HEALTH	3
FLAMMABILITY	0
REACTIVITY	0
PERSONAL	D



### PACKAGING INFORMATION

50 lb. pails.